

### FUTURELIGHT Set 4x EYE-7 RGBW Zoom + Case

4x PRO washlight with very large zoom range including PRO flightcase with wheels

Art. No.: 20000228

GTIN:











# The article is no longer in our assortment.

Features: Logistic

#### **FUTURELIGHT EYE-7 RGBW Zoom LED Moving Head Wash**

PRO washlight, compact with RGBW color mixing and very large zoom range

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution made in Sweden)
- Compact housing
- High PAN/TILT speed
- Exact positioning via 16 bit PAN/TILT movement resolution
- Master dimmer
- Motorized zoom with 2 41° beam angle
- Each color of the 7 RGBW LEDs can be switched individually
- Color presets
- Preset color temperatures
- Built-in programs
- Animated and static macros
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset

- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 7 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor-driven
- Beam effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- Flicker-free
- With a beam angle of 2° 41°

#### Package contents

1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x xLR cable

#### **ROADINGER Flightcase 4x EYE-7 RGBW Zoom**

PRO flightcase for 4 x EYE-7 Zoom LED Washer)

- With 4 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

# Technical specifications: Weight: 56,10 kg

#### FUTURELIGHT EYE-7 RGBW Zoom LED Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	7 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)

Auto position correction (feedback)	Max. TILT movement:	270° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Max. PAN movement:	
DMX channels:         18; 19; 20; 50           DMX input:         1 x 5-pin XLR (M) mounting version           DMX output:         1 x 5-pin XLR (F) mounting version           Cooling:         Temperature-controlled fan           Control:         RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone           Preprogrammed in:         LED PC-Control 512           Projection:         Flicker-free           Beam angle:         2° - 41°           Beam angle (1/2 peak):         2 - 23°           Beam angle (1/10 peak):         6 - 41°           Illuminance in Lux (Ix):         Narrow red (R) 3m: 1197 Ix, 6m: 329 Ix Narrow blue (B) 3m: 560 Ix, 6m: 824 Ix Narrow blue (B) 3m: 560 Ix, 6m: 144 Ix Narrow cold white (CW) 3m: 3792 Ix, 6m: 976 Ix Narrow all 3m: 7966 Ix, 6m: 2056 Ix Wide red (R) 3m: 82 Ix, 6m: 2056 Ix Wide red (R) 3m: 82 Ix, 6m: 23 Ix Wide green (G) 3m: 230 Ix, 6m: 61 Ix Wide cold white (CW) 3m: 266 Ix, 6m: 72 Ix Wide all 3m: 559 Ix, 6m: 151 Ix           Housing color:         Black           Dimensions:         Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm           Height: 34,7 cm         Height: 34,7 cm           G,00 kg	Flash rate:	0 - 18 Hz
DMX input:  1 x 5-pin XLR (M) mounting version  DMX output:  1 x 5-pin XLR (F) mounting version  Cooling:  Temperature-controlled fan  Control:  RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone  Preprogrammed in:  LED PC-Control 512  Projection:  Flicker-free  Beam angle:  2° - 41°  Beam angle (1/2 peak):  2 - 23°  Beam angle (1/10 peak):  6 - 41°  Illuminance in Lux (Ix):  Narrow red (R) 3m: 1197 Ix, 6m: 329 Ix Narrow green (G) 3m: 3225 Ix, 6m: 824 Ix Narrow green (G) 3m: 3225 Ix, 6m: 976 Ix Narrow all 3m: 7966 Ix, 6m: 2056 Ix Wide red (R) 3m: 82 Ix, 6m: 23 Ix Wide green (G) 3m: 230 Ix, 6m: 61 Ix Wide blue (B) 3m: 559 Ix, 6m: 72 Ix Wide all 3m: 559 Ix, 6m: 151 Ix  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Equipment:	Zoom motor-driven
DMX output:  1 x 5-pin XLR (F) mounting version  Temperature-controlled fan  Control:  RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone  Preprogrammed in:  LED PC-Control 512  Projection:  Beam angle:  2° - 41°  Beam angle (1/2 peak):  2 - 23°  Beam angle (1/10 peak):  6 - 41°  Illuminance in Lux (lx):  Narrow red (R) 3m: 1197 lx, 6m: 329 lx Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 23 lx, 6m: 61 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide dold white (CW) 3m: 259 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	DMX channels:	18; 19; 20; 50
Cooling:  Temperature-controlled fan  Control:  RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone  Preprogrammed in:  LED PC-Control 512  Projection:  Beam angle:  2° - 41°  Beam angle (1/2 peak):  2 - 23°  Beam angle (1/10 peak):  6 - 41°  Illuminance in Lux (lx):  Narrow red (R) 3m: 1197 lx, 6m: 329 lx Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	DMX input:	1 x 5-pin XLR (M) mounting version
Control:  RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone  Preprogrammed in:  LED PC-Control 512  Projection:  Flicker-free  Beam angle:  2° - 41°  Beam angle (1/2 peak):  6 - 41°  Illuminance in Lux (lx):  Narrow red (R) 3m: 1197 lx, 6m: 329 lx Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm  Depth: 17,9 cm  Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	DMX output:	1 x 5-pin XLR (F) mounting version
solution upgradeable; Sound to light via Microphone  Preprogrammed in:  LED PC-Control 512  Projection:  Flicker-free  Beam angle:  2° - 41°  Beam angle (1/2 peak):  2 - 23°  Beam angle (1/10 peak):  6 - 41°  Illuminance in Lux (lx):  Narrow red (R) 3m: 1197 lx, 6m: 329 lx Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Cooling:	Temperature-controlled fan
Projection: Flicker-free  Beam angle: 2° - 41°  Beam angle (1/2 peak): 2 - 23°  Beam angle (1/10 peak): 6 - 41°  Illuminance in Lux (lx): Narrow red (R) 3m: 1197 lx, 6m: 329 lx	Control:	solution upgradeable; Sound to light via
Beam angle   2° - 41°	Preprogrammed in:	LED PC-Control 512
Beam angle (1/2 peak):  2 - 23°  Beam angle (1/10 peak):  6 - 41°  Illuminance in Lux (lx):  Narrow red (R) 3m: 1197 lx, 6m: 329 lx  Narrow green (G) 3m: 3225 lx, 6m: 824 lx  Narrow blue (B) 3m: 560 lx, 6m: 144 lx  Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx  Narrow all 3m: 7966 lx, 6m: 2056 lx  Wide red (R) 3m: 82 lx, 6m: 23 lx  Wide green (G) 3m: 230 lx, 6m: 61 lx  Wide blue (B) 3m: 40 lx, 6m: 11 lx  Wide cold white (CW) 3m: 266 lx, 6m: 72 lx  Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm  Depth: 17,9 cm  Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak): 6 - 41°	Beam angle:	2° - 41°
Narrow red (R) 3m: 1197 lx, 6m: 329 lx Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/2 peak):	2 - 23°
Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx Wide all 3m: 559 lx, 6m: 151 lx  Housing color:  Black  Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/10 peak):	6 - 41°
Dimensions:  Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm  Weight:  6,00 kg  Legal specifications  Special product:  Not designed for household room illumination	Illuminance in Lux (Ix):	Narrow green (G) 3m: 3225 lx, 6m: 824 lx Narrow blue (B) 3m: 560 lx, 6m: 144 lx Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx Narrow all 3m: 7966 lx, 6m: 2056 lx Wide red (R) 3m: 82 lx, 6m: 23 lx Wide green (G) 3m: 230 lx, 6m: 61 lx Wide blue (B) 3m: 40 lx, 6m: 11 lx Wide cold white (CW) 3m: 266 lx, 6m: 72 lx
Depth: 17,9 cm Height: 34,7 cm  Weight: 6,00 kg  Legal specifications  Special product: Not designed for household room illumination	Housing color:	Black
Legal specifications  Special product:  Not designed for household room illumination	Dimensions:	Depth: 17,9 cm
Special product: Not designed for household room illumination	Weight:	6,00 kg
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

## ROADINGER Flightcase 4x EYE-7 RGBW Zoom

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated

Middle compartment:	10,5 cm x 38 cm
Inside dimensions:	72,5 cm x 48 cm x 47 cm
Device compartment:	25 cm x 38 cm
Dimensions:	Width: 75 cm
	Depth: 49,5 cm
	Height: 62 cm
Weight:	20,20 kg