

FUTURELIGHT Set 4x DMB-160 LED Moving-Head + Case

4x PRO beam Moving Head with 150 W COB LED including PRO flightcase with wheels

Art. No.: 20000242 GTIN: 4026397593631







The article is no longer in our assortment.

Features:

4x PRO beam Moving Head with 150 W COB LED including PRO flightcase with wheels

- Positioning within PAN and TILT

FUTURELIGHT DMB-160 LED Moving Head

PRO beam moving-head with 150 W COB LED and many features

- With glass lens
- Extremely high light output
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 1 powerful LED 150 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 270° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; Prism 6-fold Linear; Prism 8-fold rotating; frost filter; Focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397593631

Weight: 132,90 kg Length: 1.20 m Width: 0.80 m Heigth: 1.30 m Bulky product

- Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone
- Flicker-free
- With a beam angle of 3°
- Multicolor LCD display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; Light Captain

Package contents

- 1 x moving light, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x mounting bracket, 1 x xLR cable

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Trunk case with castors, PRO version

- For optimal security
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT DMB-160 LED Moving Head

100-240 V AC, 50/60 Hz
200 W
IP20
Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
1 x PowerCON (gray), mounting version
LED lamp
1 x 150 W COB (chip-on-board) cold white (CW)
270° Exact positioning (16 bit resolution) Auto position correction (feedback)
540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Gobo wheel with static gobos; Prism 6-fold Linear; Prism 8-fold rotating; frost filter; Focus motor-driven
Color wheel with 14 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
Gobo wheel with static gobos, 17 gobos and open
Shake effect
11; 13; 14; 17
1 x 3-pin XLR (M) mounting version
1 x 5-pin XLR (M) mounting version
1 x 3-pin XLR (F) mounting version
1 x 5-pin XLR (F) mounting version

RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone LED PC-Control 512; Light Captain Flicker-free 3° 3° Cold white (CW) 3m: 76776 lx, 6m: 18482 lx
Flicker-free 3° 3°
3°
3°
Cold white (CW) 3m: 76776 lx, 6m: 18482 lx
Black
Multicolor LCD display
Width: 34,3 cm Depth: 25 cm Height: 42,8 cm
15,55 kg
Class 3 (clearly perceptible sounds)
Not designed for household room illumination
Show effect lighting
_

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	29,5 cm x 27 cm x 41 cm
Middle compartment:	9,5 cm x 54 cm x 46,5 cm
Inside dimensions:	94,5 cm x 56 cm x 46,5 cm
Dimensions:	Width: 1,025 m
	Depth: 60,5 cm
	Height: 72 cm
Weight:	41,90 kg