



The article is no longer in our assortment.

Features:

EUROLITE LED TSL-1200 Scan

Scanner with 120 W LED, gobos, rotating prism, color wheel, motorized focus

- Equipped with a 120 W COB LED
- 13 or 15 DMX channel mode selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Internal programs
- Color wheel with 8 dichroic color filters and white
- Rainbow effect with adjustable speed
- Gobo-wheel with 7 rotating gobos plus open
- Gobo shake function
- Rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer
- Lightbeam with 14° radiation angle
- Control board with graphic LC display and four operating buttons for adjusting the DMX starting address, PAN/TILT reverse
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven
- Gobo effect
- Color wheel with 8 dichroic filters plus open

Logistic

- Gobo wheel with rotating gobos, 7 gobos and open
- The device is cooled by cooling fan
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

ROADINGER Flightcase 2x TSL-750/TSL-1200

Trunk case

- With 2 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 30,40 kg

EUROLITE LED TSL-1200 Scan

| | |
|---------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 165 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED: | 1 x 120 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 80° Exact positioning (16 bit resolution) |
| Max. PAN movement: | 175° Exact positioning (16 bit resolution) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven |
| Color generation: | Color wheel with 8 dichroic filters plus open |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open |
| DMX channels: | 13; 15 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; stand-alone; Sound to light via Microphone |

| | |
|------------------------|---|
| Preprogrammed in: | Light J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 14° |
| Beam angle (1/2 peak): | 14° |
| Housing color: | Black |
| Dimensions: | Width: 26 cm Depth: 47,5 cm Height: 22,5 cm |
| Weight: | 8,45 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x TSL-750/TSL-1200

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Carrying handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 23 cm x 27 cm x 46 cm |
| Middle compartment: | 10,5 cm x 29 cm x 46 cm |
| Inside dimensions: | 64 cm x 29 cm x 46 cm |
| Dimensions: | Width: 68,5 cm Depth: 33,5 cm Height: 57 cm |
| Weight: | 13,50 kg |