

# OMNITRONIC Set VFM-215AP + VFM-215A + WS-1T + WS-1R + Speaker stand MOVE MK2

GTIN:



**The article is no longer in our assortment.**

## Features:

## Logistic

### OMNITRONIC VFM-215AP 2-Way Speaker, active

Active 2-way speaker system (15") with 150 W RMS for PA and DJ applications with audio player and Bluetooth

- SD card slot and USB port
- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- 2-way bass-reflex system with 38 cm woofer and 2.5 cm tweeter
- 2 mic inputs with separate level controls
- Line input, RCA
- Master control with 2-band EQ
- Control via IR remote control; Bluetooth
- Trolley
- For application areas such as: Mobile djs / entertainer; mobile use; sports centres/gyms
- Black metal grille
- 2 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand

#### Package contents

- 1 x remote control, 1 x user manual, 1 x compact cabinet speaker, 1 x battery, 1 x power cord, 1 x declaration of conformity

### OMNITRONIC VFM-215A 2-Way Speaker, active

Active speaker with 15" woofer, 1" driver, 150 W RMS

- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- 2-way bass-reflex system with 38 cm woofer and 2.5 cm tweeter
- 2 mic inputs with separate level controls
- Line input, RCA

- Master control with 2-band EQ
- Trolley
- For application areas such as: Mobile djs / entertainer; mobile use; sports centres/gyms
- Black metal grille
- 2 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand

**Package contents**

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord

**OMNITRONIC WS-1T 2.4GHz Transmitter**

Digital audio transmission system 2.4 GHz, with USB

- Digital transmitter for wireless transmission of stereo audio signals with 2.4 GHz
- Transmit music via radio from your PC or MP3 player anywhere in your home with outstanding audio quality
- Connects USB devices (PC, smartphone, tablet PC) or audio devices with line level (e.g. CD player)
- Digital transmission in the 2.4 GHz range provides for high resistance to interference and unique sound quality (16 bits/48 kHz)
- Stereo audio input: mini USB 2.0 port or RCA L/R
- Selectable source of signal (USB or line input)
- Push button for pairing with the receiver
- Detachable rod antenna
- Operation via included power adapter or USB port
- Rugged, compact metal housing
- Incl. USB cable
- 2.4 GHz - license-free worldwide
- Control via Wi-Fi
- Operating range up to 50m in the open air
- Operating range up to 30m in buildings
- 2.4 GHz license-free worldwide
- Sample rate: 48 kHz
- The device can be connected via USB to the PC

**OMNITRONIC WS-1R 2.4GHz Receiver**

Digital audio transmission system 2.4 GHz

- Digital receiver for wireless reception of stereo audio signals with 2.4 GHz
- Transmit music via radio from your PC or MP3 player to your stereo or active speaker with outstanding audio quality
- Simultaneous operation of an unlimited number of receivers possible
- Digital transmission in the 2.4 GHz range provides for high resistance to interference and unique sound quality (16 bits/48 kHz)
- Operating range up to 30 m indoors and up to 50 m outdoors
- Stereo audio output: RCA L/R
- Push button for pairing with the transmitter
- Removable rod antenna
- Operation via supplied power unit
- Rugged, compact metal housing
- Supports PC and Mac
- 2.4 GHz ISM band - license-free worldwide
- Control via Wi-Fi
- Operating range up to 50m in the open air
- Operating range up to 30m in buildings
- 2.4 GHz license-free worldwide

**OMNITRONIC Speaker Stand MOVE MK2 set**

2 speaker stands, extendible up to 183 cm, maximum load 30 kg + carrying bag

- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height

**Package contents**

- 1 x bag

## OMNITRONIC RCA cable 2x2 0.6m

Stereo audio cable with RCA plugs

- 1 x rCA cable

## Technical specifications:

---

Weight: 32,29 kg

---

## OMNITRONIC VFM-215AP 2-Way Speaker, active

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 300W Rated: 150W RMS
Frequency range:	45 - 20000 Hz
Max. SPL:	122 dB
Control:	IR remote control; Bluetooth
Audio player:	USB + SD + Bluetooth
Attachment system:	Flange: Ø 35mm
Status LED:	Power, clip
Connections:	Input: Microphone via 2 x 6.3 mm plug (unbal.) Input: Microphone via 2 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x stereo RCA
Input channels:	2 x mono via XLR or jack, channel control via Rotary dial  1 x stereo with Line-player switch via RCA or player, channel control via Rotary dial
Equalizer:	Master: 1 x 2-band tone control
Music format:	MP3, WAV
Number of files:	Max. 999
Available storage media:	USB devices/SD cards (FAT 32)
Speaker:	1 x woofer 15" with ferrit magnet Voice coil lows 2" 1 x compression tweeter highs 1" with ferrit magnet 1 x Voice coil compression tweeter highs 1" Horn vent 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	2 pc/pcs
Transport aid:	Trolley
Material:	Plastic
Dimensions:	Width: 48 cm Depth: 39,5 cm

	Height: 74 cm
Weight:	13,35 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in

#### OMNITRONIC VFM-215A 2-Way Speaker, active

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 300W Rated: 150W RMS
Frequency range:	45 - 20000 Hz
Max. SPL:	122 dB
Attachment system:	Flange: Ø 35mm
Connections:	Input: Microphone via 2 x 6.3 mm plug (unbal.) Input: Microphone via 2 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x stereo RCA
Input channels:	2 x mono via XLR or jack, channel control via Rotary dial 1 x stereo with Line-player switch via RCA or player, channel control via Rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	1 x woofer 15" with ferrit magnet Voice coil lows 2" 1 x compression tweeter highs 1" with ferrit magnet 1 x Voice coil compression tweeter highs 1" Horn vent 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	2 pc/pcs
Transport aid:	Trolley
Material:	Plastic
Dimensions:	Width: 48 cm Depth: 39,5 cm Height: 74 cm
Weight:	13,30 kg

#### OMNITRONIC WS-1T 2.4GHz Transmitter

Type:	Audio transmission
Power supply:	5 V DC 500 mA
Power connection:	Mains input via micro USB (F) mounting version power supply cord with AC adapter (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>96 dB

THD:	<0,03 % at 1 kHz
Control:	Wi-Fi
Range:	Range up to 50m in the open air Range up to 30m in buildings
Frequency band:	2.4 GHz
Modulation:	GFSK, stereo
Frequency selection:	32
Sample rate:	48 kHz
Crosstalk:	>-96 dB
Control elements:	Source selector, power switch, connect
Connections:	Antenna via 1 x SMA (F) mounting version Input: line via 1 x stereo RCA Input: line via 1 x micro USB (F) mounting version
USB port:	1 x USB 2.0, Typ micro USB (F) mounting version
Converter:	16 bit
Material:	Metal
PC connect:	Via USB
Dimensions:	Width: 11 cm Depth: 6,5 cm Height: 6,3 cm
Weight:	220 g

#### OMNITRONIC WS-1R 2.4GHz Receiver

Type:	Audio transmission
Power connection:	Mains input via USB, type B power supply cord with AC adapter (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>96 dB
Control:	Wi-Fi
Range:	Range up to 50m in the open air Range up to 30m in buildings
Frequency band:	2.4 GHz
Material:	Metal
Dimensions:	Width: 11 cm Depth: 6,5 cm Height: 6,3 cm
Weight:	220 g
Power supply:	5 V DC, 500 mA via USB port or supplied PSU
Carrier frequency:	2406-2472 MHz (ISM), 32 channels
Modulation:	GFSK
THD:	-70 dB
Crosstalk:	-96 dB
USB port:	2.0, type mini B
Line output:	RCA L/R

Converter:	16 bits
Sample rate:	48 kHz

#### **OMNITRONIC Speaker Stand MOVE MK2 set**

Maximum carrying capacity:	30 kg
Tube diameter sector:	35
Height:	Maximum: 183 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel; Steel
Color:	Black
Weight:	5,10 kg

#### **OMNITRONIC RCA cable 2x2 0.6m**

Cable construction:	2 x 0,22 mm <sup>2</sup> Audio cable
Cable length:	0,6 m
Plug A:	2 x RCA (M)
Plug B:	2 x RCA (M)
Color:	Black
Weight:	50 g