

EUROLITE Set PAR-30 Spot bk + PAR-30 230V SMD 11W E-27 LED 3000K Art. No.: 20000284

PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN







List price: 35.58 €

incl. 19% VAT.

Features: Logistic

EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With Mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

PAR-30 LED lamp

- Easy lamp replacement
- Energy-saving
- Hot restrike
- Easy installation
- Good color rendering index (CRI)

Technical specifications:

Weight:	720 g
Weight.	720 g

EUROLITE PAR-30 Spot black

Power supply: 230 V AC, 50 Hz Power consumption: Max. 100 W IP classification: IP20 Protection class: Protection class I Suitable lamp: Max. 230 V/100 W E27 Power connection: Fixed power supply cord with safety plug Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm	EUROLITE PAR-30 Spot black	
Protection class:	Power supply:	230 V AC, 50 Hz
Protection class: Protection class I Suitable lamp: Max. 230 V/100 W E27 Power connection: Fixed power supply cord with safety plug Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Power consumption:	Max. 100 W
Suitable lamp: Max. 230 V/100 W E27 Power connection: Fixed power supply cord with safety plug Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	IP classification:	IP20
Power connection: Fixed power supply cord with safety plug Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Width: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Protection class:	Protection class I
Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Suitable lamp:	Max. 230 V/100 W E27
Cable length: Approx. 0,4 m Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Power connection:	Fixed power supply cord with safety plug
Base: E27 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Diameter: Ø 9,4 cm	Cable construction:	3 x 0,75 mm² H05SS-F
Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Cable length:	Approx. 0,4 m
Color generation: Control: Plug and play Construction: PAR-30 Housing color: Black Attachment system: Material: Aluminum Slot for spot length: Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Base:	E27
Control: Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: Diameter mounting holes: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 22,6 cm Width: 12,6 cm Width: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Lamp type:	Selectable
Construction: PAR-30 Housing color: Black Attachment system: Mounting bracket Material: Aluminum Slot for spot length: Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Uiameter: Ø 9,4 cm	Color generation:	Via color filter frame
Housing color: Attachment system: Material: Slot for spot length: Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: Diameter mounting holes: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 23,6 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Control:	Plug and play
Attachment system: Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Construction:	PAR-30
Material: Aluminum Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Housing color:	Black
Slot for spot length: 12,8 cm x 12,8 cm Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Attachment system:	Mounting bracket
Dimensions: Length: 23,5 cm Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Material:	Aluminum
Width: 14,5 cm Height: 21 cm Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Slot for spot length:	12,8 cm x 12,8 cm
Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Dimensions:	Length: 23,5 cm
Weight: 530 g Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm		·
Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm		
Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm		530 g
Material: Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm		
Color: Black Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Diameter mounting holes:	2 x Ø10mm
Filter frame Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Material:	Aluminum, 3 mm
Shape: Octagonal Material: Aluminum, 0,5 mm Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Color:	Black
Material: Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Filter frame	
Color: Black Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Shape:	Octagonal
Dimensions: Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm	Material:	Aluminum, 0,5 mm
Width: 12,6 cm Diameter: Ø 9,4 cm	Color:	Black
Diameter: Ø 9,4 cm	Dimensions:	Length: 12,6 cm
Weight: 22 g		
	Weight:	22 g

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

Voltage (lamps):	230 V
Nominal wattage:	11 W
Base:	E27
Lamp type:	LED lamp; non-clear lamp; high voltage lamp; sealed beam lamp
Lamp specification:	Hot restrike
Beam angle:	50°
Color of light:	White
Color temperature:	3000K
Setup:	Easy installation
Color rendering index (CRI):	82 Ra
Lead time:	0,2 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm
Wavelength:	605 nm
Dimensions (LxD):	92x95 mm
Weight:	190 g
Energy efficiency class (A - G):	F