

EUROLITE Set PAR-30 Spot sil + PAR-30 230V SMD 11W E-27 LED 3000K Art. No.: 2000285
PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN:



List price: 35.58 €

incl. 19% VAT.

Features:

EUROLITE PAR-30 Spot silver

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With Mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

Logistic

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

PAR-30 LED lamp

- Easy lamp replacement
- Energy-saving
- Hot restrike
- Easy installation
- Good color rendering index (CRI)

Technical specifications:

Weight: 660 g

EUROLITE PAR-30 Spot silver

Power supply: 230 V AC, 50 Hz

Power consumption: Max. 100 W

IP classification: IP20

Protection class: Protection class I

Power connection: Fixed power supply cord with safety plug

Cable length: Approx. 0,4 m

Base: E27

Lamp type: Selectable

Color generation: Via color filter frame

Control: Plug and play

Construction: PAR-30

Housing color: Silver

Attachment system: Mounting bracket

Material: Aluminum

Slot for spot length: 12,8 cm x 12,8 cm

Dimensions: Length: 23,5 cm
Width: 14,5 cm
Height: 21 cm

Weight: 470 g

Mounting bracket

Material: Aluminum

Filter frame

Material: Aluminum

Dimensions: Length: 12,6 cm
Width: 12,6 cm
Diameter: Ø 9,4 cm

Weight: 18 g

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

Voltage (lamps): 230 V

Nominal wattage: 11 W

Base: E27

Lamp type: LED lamp; non-clear lamp; high voltage lamp;
sealed beam lamp

Lamp specification: Hot restrike

Beam angle: 50°

Color of light:	White
Color temperature:	3000K
Setup:	Easy installation
Color rendering index (CRI):	82 Ra
Lead time:	0,2 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm
Wavelength:	605 nm
Dimensions (LxD):	92x95 mm
Weight:	190 g
Energy efficiency class (A - G):	F