



Features:

EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - When fog is used, this effect becomes especially attractive
 - Laser; multi beam effect; strobe effect; flower effect
 - 37 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; mobile djs / entertainer; party room; restaurants, bars and hotels; wedding/gala/events
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 3 W SMD 8072 3in1 R/G/B (homogenous color mix)
2 spots controlled separately
 - With a beam angle of 13°
- light effect**
- 3 LEDs 1 W SMD 8072 R/G/B
2 spots controlled separately
- bar**

Logistic

- 4 LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

Technical specifications:

Weight: 12.50 kg

EUROLITE LED KLS Laser Bar FX Light Set

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 50 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Device fuse: | 5 x 20 mm, F 1 A fuse replaceable |
| Lamp type: | LED lamp |
| Flash rate: | 0 - 30 Hz |
| DMX channels: | 3; 5; 9; 27 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function |
| Fixtures available for: | Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Housing color: | Black |
| Attachment system: | Tube: 1x Ø 35mm 2x mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 109 cm Depth: 14.5 cm Height: 37 cm |
| Weight: | 9.05 kg |
| Noise classification: | Class 2 (slight noise) |
| LED type: | 3 x 1 W SMD 8072 R/G/B |
| LED type: | 3 x 3 W SMD 8072 3in1 R/G/B (homogenous color mix) |
| Beam angle: | 13° |

| | |
|-------------------------|---|
| Beam angle (1/2 peak): | 13° |
| Beam angle (1/10 peak): | 20° |
| Battery: | 1 x 9.0 V E block 6LR61 alkaline manganese included |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Laser class: | 2M |
| Laser color: | R/G |
| Laser module: | Red (R) 100 mW 650nm Green (G) 30 mW 532nm |
| LED type: | 4 x 1 W SMD 8072 cold white (CW) |
| Beam angle (1/2 peak): | 7° |

OMNITRONIC Speaker System Stand alu bk

| | |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 30 kg |
| Height: | Maximum: 230 cm Minimum: 140 cm |
| Type (general stands): | Speaker stand/manual |
| Material: | Aluminum |
| Color: | Black |
| Weight: | 3.45 kg |
| Maximum load: | 30 kg |
| Maximum load (DIN15560): | 18 kg |
| Minimum height: | 1.40 m |
| Maximum height: | 2.20 m |

Scope of delivery:

1 x user manual
 1 x declaration of conformity
 1 x power cord
 1 x foot control
 1 x remote control
 2 x battery
 2 x mounting bracket
 2 x knurled screw
 1 x bag
 2 x washer