



The article is no longer in our assortment.

Features:

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
 - Compact lightweight
 - Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - When fog is used, this effect becomes especially attractive
 - For application areas such as: Wedding/gala/events; mobile use; Clubs/dancing school; mobile djs / entertainer; Rental
 - 39 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
 - With Mounting bracket
 - Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
 - Mains input and output for power linking up to 8 units
 - Laser; multi beam effect; flower effect; UV effect; Strobe effect
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 6 powerful LEDs 6 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

Logistic

- With a beam angle of 13°
light effect
- 6 powerful LEDs 2 W high-power R/G/B
 spots controlled separately
bar
- 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately
Package contents
- 1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 1 x foot control, 2 x knurled screw, 2 x washer, 2 x mounting bracket, 1 x battery, 1 x bag

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

Technical specifications:

Weight: 13,45 kg

EUROLITE LED KLS Laser Bar PRO FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 3,15 A
Lamp type:	LED lamp
DMX channels:	3; 5; 10; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
Preprogrammed in:	EASY SHOW 1; Light J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	2x Mounting bracket
Dimensions:	Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm
Weight:	10,00 kg
Noise classification:	Class 2 (slight noise)

Power cord	
Cable length:	3 m
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Spotlight	
LED:	6 x 6 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 30 Hz
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Light effect	
LED:	6 x 2 W high-power R/G/B
Flash rate:	0 - 30 Hz
Bar	
LED:	4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m