

EUROLITE Set LED SL-350 DMX Search Light + STV-200 Follow spot stand, stainless steel

Follow spot with cold white 300 W LED including PRO version follow spot

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED SL-350 DMX Search Light

Follow spot with cold white 300 W LED for medium distances

- Manual control via control panel with buttons and faders
- 1 powerful LED 300 W COB (chip-on-board) cold white (CW)
- Focus manual; Iris stepless
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With a beam angle of 10°
- With Mounting bracket
- 4 digit 7-segment LED display
- Direct color temperature selection for 3 preset values
- Dimmer electronic
- Strobe effect
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Suitable for a range of use from to 30 meters
- Color wheel with 5 dichroic filters plus open
- For application areas such as: Wedding/gala/events; Stage; theater; Rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x mounting bracket, 1 x hex key

EUROLITE STV-200 Follow Spot Stand, Stainless Steel

PRO version with ball bearing head, maximum load 50 kg, maximum height 160 cm

- Professional follow stand for mobile lighting systems

Logistic

- Stand head lies on a ball-bearing
- Heavy-duty stainless steel version for extra stability and safety
- Easy handling
- Safety ring for height adjustment
- Adjustable height

Technical specifications:

Weight: 16,85 kg

EUROLITE LED SL-350 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	1 x 300 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 20 Hz
Equipment:	Focus manual; Iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Beam angle:	10°
Beam angle (1/2 peak):	10°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Range of use:	- 30m
Dimensions:	Length: 60 cm Width: 27,5 cm Height: 30 cm
Weight:	10,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE STV-200 Follow Spot Stand, Stainless Steel

Maximum carrying capacity:	50 kg
Height:	Maximum: 160 cm Minimum: 110 cm
Attachment system:	M12 thread
Type (general stands):	Light stand/manual
Material:	Aluminum; stainless steel
Color:	Silver
Weight:	6,30 kg