



### Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- Control via plug and play
- With mounting bracket
- Available in various colors
- For PAR 20
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- <p>OMNILUX PAR-20 230V SMD 6W E-27 LED 3000K
- <h2 class="featureSatz">PAR-20 lamp</h2>Stronger with the same power consumption
- Better brightness and color of light thanks to SMD LED
- Good color rendering index (CRI)

### Logistic

EAN / GTIN: 4026397601138

Weight: 0,60 kg

Length: 0.30 m

Width: 0.22 m

Height: 0.21 m

### Technical specifications:

Weight: 0.40 kg

Energy efficiency class (A - G): F

**EUROLITE PAR-20 Spot silver**

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-20
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8.5 cm x 8.5 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11.2 cm Diameter: Ø 8 cm
Weight:	0.32 kg
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Aluminum
Dimensions:	Length: 8.4 cm Width: 8.4 cm Diameter: Ø 6.1 cm

**OMNILUX PAR-20 230V SMD 6W E-27 LED 3000K**

Operating voltage:	230
Nominal wattage:	6 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Beam angle:	50°
Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	88 Ra
Lead time:	0.2 s
Construction:	PAR-20
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)

Lamp life:	20000 h
Luminous flux:	510 lm
Wavelength:	778 nm
Lamp current:	0.053 A
Dimensions (LxD):	86x64 mm
Weight:	0.10 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	1141930

### **Scope of delivery:**

---

- 1 x spotlight
- 1 x filter frame
- 1 x user manual