

## EUROLITE Set 4x LED PAR-56 HCL Short sw + PRO Case

4x PAR-56 Spot with 9 x 10W 6in1 LED and RGBAW+UV color mixing including PRO flightcase

Art. No.: 2000326

GTIN:



### Features:

- 9 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 4x PAR-56 Spot short
- <h2 class="featureSatz">Trunk case</h2>Detachable compartments - case can also be used as universal transport case
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

## Technical specifications:

---

Weight: 14.01 kg

---

### EUROLITE LED PAR-56 HCL Short bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	9 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	38°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting
Dimensions:	Width: 20.5 cm Depth: 17.5 cm Height: 23 cm
Weight:	1.60 kg
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø10mm; 1 x Ø8mm
Material:	Aluminum casting, 2.5 mm
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

---

**ROADINGER Flightcase 4x PAR-56 Spot short**

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	21.5 cm x 21.5 cm x 23 cm
Inside dimensions:	43 cm x 43 cm x 23 cm
Dimensions:	Width: 48.5 cm Depth: 48.5 cm Height: 31 cm
Weight:	7.60 kg

**Scope of delivery:**

---

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x user manual