

EUROLITE Set 4x LED PAR-56 HCL Short sw + EPS Case

4x PAR-56 Spot with 9 x 10W 6in1 LED and RGBAW+UV color mixing including flightcase

Art. No.: 2000327

GTIN:



List price: 1041.25 €

incl. 19% VAT.

Features:

EUROLITE LED PAR-56 HCL Short bl

PAR-56 spot with 9 x 10 W 6in1 LED and RGBAW+UV color mixing

- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Party room; Stage; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

Logistic

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 15,10 kg

EUROLITE LED PAR-56 HCL Short bl

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, F 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; IR remote control
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	38°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20,5 cm Depth: 17,5 cm Height: 23 cm
Weight:	1,79 kg
Photobiological safety:	Risk Group 0
Remote control	

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load: 25 kg

Aluminum profile frames: 30 mm

Case handle: 2 pc/pcs

Stop hinge: 2 pc/pcs

Lock: Butterfly lock: 1 pc/pcs

Material: Birch multiplex, 7 mm

Color: Dark brown, laminated

Compartment dimensions: 22 cm x 22 cm x 24 cm

Inside dimensions: 44 cm x 44 cm x 24 cm

Dimensions: Width: 48,5 cm
Depth: 48,5 cm
Height: 31 cm

Weight: 7,95 kg
