eurolite®

EUROLITE Party Set 3

CENTER



The article is no longer in our assortment.

Features:

EUROLITE LED Mini D-5 Beam Effect

Mini beam effect with LEDs in R, G, B, and W

- 24 lenses fill the room with moving colorful beams
- Practicle size, easily transportable
- 6 powerful LEDs 3 W high-power R/G/B/W/A
- Color macros changing
- Flower effect
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone
- With mounting bracket
- For application areas such as: Party room; small rental
- Very quiet working noise
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x power cord, 1 x user manual

EUROLITE LED PARty TCL Spot

Compact spotlight with 12 x 3 W 3in1 TCL RGB LED and DMX control

- 12 powerful LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
- Color change programs; color blend stepless; pulse effect adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone

Logistic

- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Party room; small rental
- Application possibility: Suspended; on stand
- Package contents
- 1 x light effect, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

EUROLITE LED Party UV Bar-9

Simple UV lighting bar with 9 x 1 W ultra violet (UV) LED

- Perfect for decorative and illumination purposes
- Slender housing
- 9 powerful LEDs 1 W high-power ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via on/off switch at cable
- With a beam angle of 30°
- With mounting bracket
- Various versions available
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; standing Package contents
- 1 x spotlight, 2 x mounting bracket, 1 x user manual

EUROLITE LED Party strobe 36

Ultra compact party strobe with high-power LEDs

- Stroboscope with 36 white SMD 5050 LEDs
- Perfect for decorations or party rooms
- Smallest dimensions, low weight
- Auto and sound mode selectable
- Built-in microphone with sensitivity control
- Variable flash rate: 1-8 flashes/second
- Low price, portable and user-friendly
- 36 powerful LEDs SMD 5050 cold white (CW)
- Strobe effect
- Control via stand-alone

EUROLITE N-10 Fog Machine black

400 watt fogger with remote control

- Output distance: Approx. 2 m
- With level indication
- Operates on water-based fluid
- Control via wired remote control
- With mounting bracket
- For application areas such as: Party room; clubs/dancing school; small rental
- Application possibility: Standing; suspended
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x filter

EUROLITE Smoke Fluid -A2D- Action Smoke Fluid 1I

Fog effect with low density and hang time

- Odorless
- Glycerine- and DEG-free composition
- Non-toxic

- Not harmful to health
- Biodegradable according to OECD 301E/EEC 84/449 C3
- Non-flammable, no transport restrictions, no hazardous material
- Permanent quality control
- Proven quality
- Water-based fluid ready for use
- Made in Europe
- For application areas such as: Wedding/gala/events; small rental; party room; clubs/dancing school

Technical specifications:

Weight:

6,54 kg

EUROLITE LED Mini D-5 Beam Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Lamp type:	LED lamp
LED type:	6 x 3 W high-power R/G/B/W/A
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Metal
	motor
Dimensions:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm
	Width: 21 cm Depth: 19,5 cm
Dimensions:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm
Dimensions: Weight:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise-
Dimensions: Weight: Noise classification:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise- sensitive environments)
Dimensions: Weight: Noise classification: Cable construction:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise-sensitive environments) 3 x 0,75 mm² H05VV-F
Dimensions: Weight: Noise classification: Cable construction: Cable length:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise-sensitive environments) 3 x 0,75 mm² H05VV-F Approx. 1,2 m
Dimensions: Weight: Noise classification: Cable construction: Cable length: Diameter mounting holes:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise-sensitive environments) 3 x 0,75 mm² H05VV-F Approx. 1,2 m 1 x Ø11mm
Dimensions: Weight: Noise classification: Cable construction: Cable length: Diameter mounting holes: Material:	Width: 21 cm Depth: 19,5 cm Height: 20,5 cm 1,95 kg Class 1 (very slight noise, suitable for noise-sensitive environments) 3 x 0,75 mm² H05VV-F Approx. 1,2 m 1 x Ø11mm Metal, 2 mm

EUROLITE LED PARty TCL Spot	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H03VVH2-F
Lamp type:	LED lamp
LED type:	12 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Flash rate:	0,5 - 16 Hz
DMX channels:	5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
Projection:	Flicker-free
PWM frequency:	15700 Hz
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	38°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15 cm Depth: 9 cm Height: 16 cm
Weight:	0,43 kg
Noise classification:	Class 2 (slight noise)
Diameter mounting holes:	1 x Ø12mm; 2 x Ø8mm
Material:	Metal, 1 mm, painted
Color:	Black, matte
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Party UV Bar-9

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	9 x 1 W high-power ultra violet (UV)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cooling:	Passive convection cooling
Control:	On/off switch at cable
Beam angle:	30°
Beam angle (1/2 peak):	30°
Wavelength:	398 nm
Housing color:	Black matte
Attachment system:	2x mounting bracket
Material:	Metal
Dimensions:	Length: 50 cm
	Depth: 6,5 cm
	Height: 6,5 cm
Weight:	0,66 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0 at 1 m
Diameter mounting holes:	1 x Ø10mm; 1 x Ø6mm
Material:	Aluminum, 2 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Party strobe 36

Power supply:	230 V AC, 50 Hz
Power consumption:	12 W
Power connection:	Fixed power supply cord with Euro plug
Cable length:	1 m
Lamp type:	LED lamp
LED type:	36 x SMD 5050 cold white (CW)
Flash rate:	1 - 8 Hz
Control:	Stand-alone
Beam angle (1/2 peak):	80°
Color temperature:	6500K
Dimensions:	Width: 10 cm
	Depth: 11 cm
	Height: 10 cm
Weight:	0,20 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE N-10 Fog Machine black

Power supply:	230 V AC, 50 Hz
Power consumption:	400 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug

Warm-up time:	Approx. 5 min
Output distance:	Approx. 2 m
Tank capacity:	0,3 I water-based fluid fixed tank
Fluid consumption:	Approx. 21 ml/min
Control:	Wired remote control
Housing color:	Black
Attachment system:	Mounting bracket
Heater:	400 W
Controls:	Overheat
Color:	Black
Dimensions:	Width: 14,5 cm Depth: 26,5 cm
	Height: 17 cm
Weight:	1,87 kg
Noise classification:	Class 3 (clearly perceptible sounds)

EUROLITE Smoke Fluid -A2D- Action Smoke Fluid 1I

Container size:	11
Type of fluid:	Water-based fluid ready for use
Weight:	1,00 kg