

RELACART Set UR-222S Condensator Handmic

Art. No.: 2000343

GTIN: 4026397607529



Features:

RELACART UR-222S 1-channel UHF Receiver 823-832 + 863-865 MHz

Multifrequency wireless receiver with high-quality diversity reception

- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Pilot frequency squelch technology delete wireless RF interference
- Automatic frequency scan (AFS) finds interference-free channels
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- 2 detachable BNC antennas allow for use with the R-14D antenna divider
- (19") 48.3 cm rack installation possible 1 U
- Operating range up to 80m
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- Up to 9 transmitters can be operated in parallel without interference
- Multicolor LCD display
- Charge status indicator
- Desktop console housing

RELACART UH-222C Microphone 823-832 + 863-865 MHz

Hand-held microphone with PLL multifrequency transmitter

- Condenser hand-held microphone with UHF pilot tone technology (PLL)
- Ergonomic aluminum alloy housing, applicable for touring
- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- RF output power Hi/Low adjustable
- Gain level Hi/Mid/Low adjustable

Logistic

EAN / GTIN: 4026397607529

Weight: 2,50 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

- Capsule M-C36
- Directly compatible with Shure's SM58 capsule
- Polar pattern: Cardioid
- Operating range up to 80m
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- OLED display
- Charge status indicator

Technical specifications:

Weight: 2.30 kg

RELACART UR-222S 1-channel UHF Receiver 823-832 + 863-865 MHz

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12V DC 1000 mA
Power consumption:	3 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Number of channels:	1
Frequency range:	45 - 18000 Hz
S/N ratio:	>105 dB
THD:	<0.7 % at 1 kHz
Range:	Range up to 80m
Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Diversity:	Antenna diversity
Switching bandwidth:	11 MHz
Frequency stability:	± 0.005 %
Parallel mode:	Max. 9 transmitter
Modulation:	FM
Frequency selection:	90 switchable frequencies In 10 groups with up to 10 preset frequencies each
Display type:	Multicolor LCD display
Display:	Charge status indicator , antenna A/B , RF signal level , AF audio level; frequency
Control elements:	Groundlift selector, menu, navigation keys
Connections:	Antenna via 2 x BNC (F) 8 V Output: microphone via 1 x 3-pin XLR (M) mounting version Output: microphone via 1 x 6.3 mm plug (unbal.)
Switch:	On/off switch
Material:	Metal
Color:	Black
Housing design:	Desktop console housing

(19") 48.3 cm rack installation possible 1 U

Dimensions:	Width: 20 cm
	Depth: 26 cm
	Height: 4.4 cm

Weight:	1.95 kg
---------	---------

RELACART UH-222C Microphone 823-832 + 863-865 MHz

Type:	Hand-held transmitter
-------	-----------------------

Power supply:	3V DC
---------------	-------

Capsule type:	Condenser
---------------	-----------

Polar pattern:	Cardioid
----------------	----------

Battery:	2 x Mignon (AA) (not included)
----------	--------------------------------

Frequency range:	100 - 18000 Hz
------------------	----------------

Sensitivity:	-52 dB
--------------	--------

Max. SPL:	145 dB
-----------	--------

Range:	Range up to 80m
--------	-----------------

Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
-----------------	--------------------------------------

Switching bandwidth:	11 MHz
----------------------	--------

RF power output:	5 mW (LO); 10 mW (HI)
------------------	-----------------------

Modulation:	FM
-------------	----

Frequency selection:	90 switchable frequencies In 10 groups with up to 10 preset frequencies each
----------------------	---

Display type:	OLED display
---------------	--------------

Display:	Charge status indicator , frequency , group , channel; Mute
----------	---

Control elements:	Gain-switch (high-mid-low), transmitter power switch (high-low)
-------------------	---

Switch:	On/off/mute switch
---------	--------------------

Material:	Aluminum
-----------	----------

Dimensions:	Length: 25.5 cm
	Diameter: Ø 5.2 cm

Weight:	0.34 kg
---------	---------

Scope of delivery:

1 x RELACART UR-222S 1-channel UHF Receiver 823-832 + 863-865 MHz

1 x receiver
1 x external mains adapter
2 x antenna
1 x jack cable
3 x mounting bracket
8 x screw
1 x user manual
1 x declaration of conformity
1 x bag

1 x RELACART UH-222C Microphone 823-832 + 863-865 MHz

1 x microphone
1 x user manual
1 x declaration of conformity