

EUROLITE Set 4x AKKU IP Flat Light 1 chrome + Case

4x flat chrome spotlight with 15 W RGBW LED including PRO flightcase

Art. No.: 20000350

GTIN: 4026397609479



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Chrome housing
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 LED 15 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; DMX
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- OLED display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing
- <p>ROADINGER Flightcase 4x AKKU Flat Light Series
- <h2 class="featureSatz">Carrying case, PRO version</h2>High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle

Logistic

EAN / GTIN: 4026397609479

Weight: 12,20 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	10.65 kg
EUROLITE AKKU IP Flat Light 1 cr	
Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 22 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; DMX
Fixtures available for:	Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	8°
Housing color:	Chrome
Attachment system:	Mounting bracket
Display type:	OLED display
Dimensions:	Width: 17.2 cm Depth: 13.8 cm Height: 6.4 cm
Weight:	1.63 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU Flat Light Series

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	8 cm x 19 cm x 10 cm
Accessory compartment:	38 cm x 6.5 cm x 12 cm
Inside dimensions:	38 cm x 27 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4.15 kg

Scope of delivery:

1 x device
 1 x external mains adapter
 1 x remote control
 1 x battery
 1 x declaration of conformity
 1 x user manual