

EUROLITE Set 2x LED TMH-X1 Moving-Head Beam + Case

2x 60 W beam, compact, narrow angle, beautiful RGBW colors including PRO flightcase

Art. No.: 20000356

GTIN:



The article is no longer in our assortment.

Features:

2x 60 W beam, compact, narrow angle, beautiful RGBW colors including PRO flightcase

- Positioning within

Logistic

EUROLITE LED TMH-X1 Moving Head Beam

60 W beam, compact, narrow angle, beautiful RGBW colors

- Compact lightweight
- 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN, 220° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color selection; color blend stepless; Dimmer electronic
- Beam effect; strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 3°
- Mains input and output for power linking up to 8 units
- OSRAM bulb included
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable

ROADINGER Flightcase 2x LED TMH-X1 Moving-Head Beam

PRO flightcase for 2 x TMH-X1

- With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	19,58 kg
---------	----------

EUROLITE LED TMH-X1 Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 10 Hz
DMX channels:	14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 3251 lx, 6m: 712 lx

Green (G) 3m: 4684 lx, 6m: 1125 lx
Blue (B) 3m: 819 lx, 6m: 220 lx
Cold white (CW) 3m: 7909 lx, 6m: 1899 lx
All 3m: 15489 lx, 6m: 3655 lx

Housing color:	Black
Use of brands:	OSRAM bulb included
Dimensions:	Width: 20,7 cm Depth: 19,6 cm Height: 31,3 cm
Weight:	4,29 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED TMH-X1 Moving-Head Beam

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10 cm x 28 cm x 26 cm
Compartment dimensions:	28 cm x 13,5 cm x 21 cm
Inside dimensions:	28 cm x 26 cm
Dimensions:	Width: 72 cm Depth: 33,5 cm Height: 39,5 cm
Weight:	11,00 kg