

EUROLITE Set 4x LED TMH-X1 Moving Head Beam + Case

4x 60 W beam, compact, narrow angle, beautiful RGBW colors including PRO flightcase

Art. No.: 2000357

GTIN: 4026397580181



Features:

- Positioning within
- <p>EUROLITE LED TMH-X1 Moving Head Beam
- <h2 class="featureSatz">60 W beam, compact, narrow angle, beautiful RGBW colors</h2>Compact lightweight
- 1 LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN, 220° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color selection; color blend stepless; Dimmer electronic
- Beam effect; strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Fixtures available for Light J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 3°
- Mains input and output for power linking up to 8 units
- OSRAM bulb included
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 4x LED TMH-X1 Moving Head Beam with wheels
- <h2 class="featureSatz">Trunk case with castors, PRO version</h2>With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

Logistic

EAN / GTIN: 4026397580181

Weight: 42,72 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.80 m

Bulky product

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 1 chrome tip-over lock
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 39.78 kg

EUROLITE LED TMH-X1 Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 10 Hz
DMX channels:	14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 3251 lx, 6m: 712 lx Green (G) 3m: 4684 lx, 6m: 1125 lx Blue (B) 3m: 819 lx, 6m: 220 lx Cold white (CW) 3m: 7909 lx, 6m: 1899 lx All 3m: 15489 lx, 6m: 3655 lx
Housing color:	Black
Use of brands:	OSRAM bulb included

Dimensions:	Width: 20.7 cm Depth: 19.6 cm Height: 31.3 cm
Weight:	4.29 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED TMH-X1 Moving Head Beam with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10.5 cm x 60 cm x 27 cm
Compartment dimensions:	27 cm x 14 cm x 27 cm
Inside dimensions:	64.5 cm x 26 cm
Dimensions:	Width: 71 cm Depth: 61 cm Height: 53 cm
Weight:	21.90 kg

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x XLR cable