



List price: 4104.31 €

incl. 19% VAT.

Features:

ALUTRUSS QUADLOCK 6082-3000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection Set

Logistic

ALUTRUSS QUADLOCK 6082C-21 2-Way Corner 90°

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 1 x connection Set

ALUTRUSS QUADLOCK 6082L-30 3-Way Corner 90°

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 2 x connection Set

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with Quick-Lock
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

Package contents

- 2 x splint, 2 x bolt

ALUTRUSS QUADLOCK End Plate QQGP-Male M-10

Baseplate for mobile use (connectors 6082 included)

- Easy installation
- The article is delivered pre-assembled
- Trusspipe: 50 mm
- Made in Europe
- Application possibility: Standing

half cone

- M10 thread

Package contents

- 1 x plate, 4 x half cone

Technical specifications:

Weight: 109,36 kg

ALUTRUSS QUADLOCK 6082-3000 4-Way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 3 m Width: 29 cm

Height: 29 cm

Weight: 14,2 kg

ALUTRUSS QUADLOCK 6082C-21 2-Way Corner 90°

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 50 cm
Width: 50 cm
Height: 29 cm

Weight: 5,50 kg

ALUTRUSS QUADLOCK 6082L-30 3-Way Corner 90°

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 50 cm
Width: 50 cm
Height: 50 cm

Weight: 7,95 kg

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

Trusspipe: 50 mm

Color: Alu colored

Weight: 90 g

ALUTRUSS QUADLOCK End Plate QQGP-Male M-10

Setup: Easy installation

Trusspipe: 50 mm

Material: Aluminum

Color: Alu colored

Dimensions: Length: 30,7 cm
Width: 30,7 cm
Height: 5 cm

Weight: 1,55 kg

Half cone

Thread: M10 thread