



The article is no longer in our assortment.

Features:

EUROLITE LED BAR-6 QCL RGBA Bar

LED bar (59cm) with 6 x 4 watt 4in1 QCL RGBA LED

- 6 powerful LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; Light J; Light Captain
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; small rental
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

EUROLITE SB-205 Soft Bag

Universal softbag

Logistic

- Ideal for e.g. LED bars with 50 cm length and accessories
- High-quality workmanship with nylon , black
- With divider
- With 2 Device compartments
- Interior with foam padding
- 2 carrying straps

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Can transmit up to 8 DMX channels
- Control via DMX; Sound to light via Microphone
- Desktop console housing

Technical specifications:

Weight: 8,72 kg

EUROLITE LED BAR-6 QCL RGBA Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	6 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling

Control:	Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; Light J; Light Captain
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Length: 59 cm Depth: 6,5 cm Height: 10 cm
Weight:	1,75 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-205 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent
Color:	Black
Dimensions:	Width: 57,5 cm Depth: 17 cm Height: 12 cm
Weight:	300 g

EUROLITE DMX LED Operator 2 controller

Pin configuration:	Inside + / outside -
Power consumption:	4,00 W
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)

DMX channels:	Output 8
Control:	DMX; Sound to light via Microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 26,5 cm Depth: 16,5 cm Height: 5,5 cm
Weight:	1,12 kg
Power supply:	230 V AC, 50 Hz, via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector