



The article is no longer in our assortment.

Features:

EUROLITE LED BAR-12 QCL RGBA Bar

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBA LED

- 12 powerful LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light´J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Silent operation
- Application possibility: Suspended; wall mounting

Package contents

- 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

Logistic

- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 x shoulder strap

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Can transmit up to 8 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing

Technical specifications:

| | |
|---------|----------|
| Weight: | 13,92 kg |
|---------|----------|

EUROLITE LED BAR-12 QCL RGBA Bar

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 24 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 4 W high-power 4in1 QCL RGBA (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 6; 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |

| | |
|--------------------------|--|
| Control: | Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Preprogrammed in: | LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Aluminum casting; metal; plastic |
| Dimensions: | Length: 110 cm Depth: 6,5 cm Height: 10 cm |
| Weight: | 2,90 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø10mm; 1 x Ø8mm; 2 x Ø7mm |
| Material: | Metal, 2 mm |
| Cable construction: | H05VV-F |
| Cable length: | Approx. 1,2 m |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE SB-12 Soft Bag

| | |
|-----------------|--|
| Maximum load: | 20 kg |
| Carrying strap: | 2 pc/pcs |
| Transport aid: | 1 x shoulder strap |
| Material: | Textile |
| Color: | Black |
| Dimensions: | Width: 107 cm Depth: 17 cm Height: 18 cm |
| Weight: | 0,60 kg |

EUROLITE DMX LED Operator 2 controller

| | |
|--------------------|---|
| Pin configuration: | Inside + / outside - |
| Power consumption: | 4,00 W |
| IP classification: | IP20 |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |

| | |
|-----------------|---|
| DMX channels: | Output 8 |
| Control: | DMX; sound to light via microphone |
| Housing color: | Black |
| Color: | Black |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 26,5 cm Depth: 16,5 cm Height: 5,5 cm |
| Weight: | 1,12 kg |
| Power supply: | 230 V AC, 50 Hz, via 12 V DC, 300 mA power unit included in the delivery |
| DMX512 output: | 3-pin XLR connector |