

EUROLITE Set 4x LED PIX-12 HCL + Controller

4x Spotlight bar with 12 x 10 W 6in1 LED including compact DMX controller

Art. No.: 20000408







The article is no longer in our assortment.

Features: Logistic

EUROLITE LED PIX-12 HCL Bar

LED bar (1m) with 12 x 10 watt 6in1 HCL RGBWA/UV LED

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect; UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- Preprogrammed in Light 'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6;
 LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units

Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

EUROLITE DMX LED EASY Operator 4x6

Compact DMX controller for 4 LED spotlights with up to 6 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBAW+UV LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, amber, white, UV and master

- Various modes for the DMX channel sequence selectable
- Manual control via 6 faders
- 2 faders for direct RGBW and A/UV mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases)
- Can transmit up to 28 DMX channels
- Control via DMX; Sound to light via Microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

Technical specifications:

Weight: 21,84 kg

EUROLITE LED PIX-12 HCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 16; 36; 74
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	41°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 1 m

	Depth: 11,5 cm Height: 16,5 cm
Weight:	5,20 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX LED EASY Operator 4x6

Power supply:	100-240 V AC, 50/60 Hz 9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases)
DMX channels:	Output 28
Control:	DMX; Sound to light via Microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 25 cm
	Depth: 11,5 cm
	Height: 5,5 cm
Weight:	1,04 kg
Noise classification:	Class 0 (no noise at all)