

## EUROLITE Set 2x LED BAR-12 QCL RGBA + Soft Bag

2x Spotlight bar with 12 x 4 W 4in1 LED including soft bag

Art. No.: 20000415

GTIN: 4026397621204



### Features:

- 12 LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>EUROLITE SB-12 Soft Bag
- <h2 class="featureSatz">Practical black soft bag for LED bars (1 m length), adjustable divider</h2>Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps

### Logistic

EAN / GTIN: 4026397621204

Weight: 9,50 kg

Length: 1.20 m

Width: 0.30 m

Height: 0.41 m

Bulky product

- 1 x shoulder strap

## Technical specifications:

|         |         |
|---------|---------|
| Weight: | 8.40 kg |
|---------|---------|

### EUROLITE LED BAR-12 QCL RGBA Bar

|                          |                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                             |
| Power consumption:       | 24 W                                                                                                                                               |
| IP classification:       | IP20                                                                                                                                               |
| Protection class:        | Protection class I                                                                                                                                 |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                   |
| Power output:            | 1 x IEC connector (F) mounting version                                                                                                             |
| Lamp type:               | LED lamp                                                                                                                                           |
| LED type:                | 12 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)                                                                                           |
| Flash rate:              | 0 - 20 Hz                                                                                                                                          |
| DMX channels:            | 2; 4; 5; 6; 9                                                                                                                                      |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                     |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                     |
| Cooling:                 | Passive convection cooling                                                                                                                         |
| Control:                 | Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Fixtures available for:  | LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light´J; Colorchief                     |
| Projection:              | Flicker-free                                                                                                                                       |
| Beam angle:              | 17°                                                                                                                                                |
| Beam angle (1/2 peak):   | 17°                                                                                                                                                |
| Housing color:           | Black                                                                                                                                              |
| Attachment system:       | Mounting bracket                                                                                                                                   |
| Display type:            | 4 digit 7-segment LED display                                                                                                                      |
| Material:                | Aluminum casting; metal; plastic                                                                                                                   |
| Dimensions:              | Length: 110 cm<br>Depth: 6.5 cm<br>Height: 10 cm                                                                                                   |
| Weight:                  | 2.90 kg                                                                                                                                            |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                          |
| Photobiological safety:  | Risk Group 0                                                                                                                                       |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø10mm; 1 x Ø8mm; 2 x Ø7mm                                                                                                           |

|                     |                                              |
|---------------------|----------------------------------------------|
| Material:           | Metal, 2 mm                                  |
| Cable construction: | H05VV-F                                      |
| Cable length:       | Approx. 1.2 m                                |
| Special product:    | Not designed for household room illumination |
| Intended use:       | Show effect lighting                         |

#### **EUROLITE SB-12 Soft Bag**

|                 |                                                |
|-----------------|------------------------------------------------|
| Maximum load:   | 20 kg                                          |
| Carrying strap: | 2 pc/pcs                                       |
| Transport aid:  | 1 x shoulder strap                             |
| Material:       | Textile                                        |
| Color:          | Black                                          |
| Dimensions:     | Width: 107 cm<br>Depth: 17 cm<br>Height: 18 cm |
| Weight:         | 0.60 kg                                        |

#### **Scope of delivery:**

1 x light effect  
 2 x mounting bracket  
 1 x power cord  
 2 x knurled screw  
 2 x washer  
 1 x user manual