

## OMNITRONIC Set 2x XKB-212A + Speaker Stand MOVE MK2

Active speaker set with 2x XKB-212A, 2x high-quality stands including bag, 2x XLR cable

Art. No.: 20000421

GTIN: 4026397622799



### Features:

- Active PA speaker system for touring applications and permanent installations
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Digital signal processor
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- Control via Bluetooth
- LCD display
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer
- <p>OMNITRONIC Speaker Stand MOVE MK2 set
- <h2 class="featureSatz">2 speaker stands, extendible up to 183 cm, maximum load 30 kg + carrying bag</h2>Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height
- <p>OMNITRONIC XLR Cable 3-pin 10m bk
- <h2 class="featureSatz">Audio cable with 3-pin XLR connectors</h2>

### Logistic

EAN / GTIN: 4026397622799

Weight: 40,00 kg

Length: 1.00 m

Width: 0.82 m

Height: 0.68 m

## Technical specifications:

---

Weight: 36.44 kg

---

### OMNITRONIC XKB-212A 2-way Speaker, active, DSP

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	800 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Power:	Program: 600W Rated: 60W RMS HF Rated: 300W RMS LF
Frequency range:	55 - 20000 Hz
Sensitivity:	95 dB
DSP:	Digital signal processor
DSP presets:	LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
Dispersion angle:	90° x 50°
Control:	Bluetooth
Bluetooth device name:	Omnitronic
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Display type:	LCD display
Control elements:	Master control, encoder
Controls:	Limiter
Status LED:	Power, signal, limit
Connections:	Output: line via 1 x 3-pin XLR
Input channels:	2 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 3-band tone control
Speaker:	1 x woofer 12" Voice coil lows 2.4" with ferrit magnet Voice coil compression tweeter highs 1.35"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Material:	Plastic
Color:	Black
Dimensions:	Width: 38 cm Depth: 35 cm

	Height: 61 cm
Weight:	14.90 kg

#### **OMNITRONIC Speaker Stand MOVE MK2 set**

Maximum carrying capacity:	30 kg
Tube diameter sector:	35
Height:	Maximum: 183 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel; steel
Color:	Black
Weight:	5.10 kg

#### **OMNITRONIC XLR Cable 3-pin 10m bk**

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.46 kg

#### **Scope of delivery:**

##### **2 x OMNITRONIC XKB-212A 2-way Speaker, active, DSP**

1 x compact cabinet speaker  
1 x power cord  
1 x user manual  
1 x declaration of conformity

##### **1 x OMNITRONIC Speaker Stand MOVE MK2 set**

1 x bag

##### **2 x OMNITRONIC XLR Cable 3-pin 10m bk**

1 x XLR cable