



The article is no longer in our assortment.

Features:

EUROLITE LED KLS-801 Compact Light Set

Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

Logistic

- Control via stand-alone; DMX; foot switch (optional); sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 30°
- TV spigot
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x spotlight, 1 x bag

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

Technical specifications:

Weight:	25,75 kg
---------	----------

EUROLITE LED KLS-801 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	90,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED type:	7 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version

DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; foot switch (optional); sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11,75 kg
Dimensions:	Width: 120 cm Depth: 6,5 cm Height: 31,5 cm
Dimensions:	Width: 125 cm Depth: 12 cm Height: 38 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm
Weight:	2,25 kg
Noise classification:	Class 0 (no noise at all)