

EUROLITE Set 4x LED SLS-7 HCL Floor + 2x LED FE-700 + DMX LED Color Chief Controller

4x LED spotlight, 2x DMX lighting effect with beams including DMX lighting desk

GTIN:



List price: 1069.81 €

incl. 19% VAT.

Features:

EUROLITE LED SLS-7 HCL Floor

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

Logistic

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

EUROLITE LED FE-700 Flower Effect

DMX lighting effect with beams in the colors R, G, B, W, A and P, incl. IR remote control

- Precision lenses fill the room with countless rotating beams
- 6 powerful LEDs 3 W high-power R/G/B/W/A/P
- Rotation speed stepless
- Multi beam effect; flower effect; Strobe effect
- 3 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Programmable 24 scenes/chases distributed over 1 page(s)
- Can transmit up to 240 DMX channels
- Control via DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
- (19") 48.3 cm rack installation 3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; Party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Firmware can be updated

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

Technical specifications:

Weight: 14,77 kg

EUROLITE LED SLS-7 HCL Floor

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	20 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	39°
Wavelength:	Ultra violet (UV) 400 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	Plastic; metal; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1,38 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black

Remote control

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE LED FE-700 Flower Effect

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 24 W

IP classification: IP20

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power output: 1 x IEC connector (F) mounting version

Lamp type: LED lamp

LED: 6 x 3 W high-power R/G/B/W/A/P

DMX channels: 3; 10

DMX input: 3-pin XLR (M) mounting version

DMX output: 3-pin XLR (F) mounting version

Cooling: Passive convection cooling

Control: Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function

Preprogrammed in: Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2

Housing color: Black

Attachment system: Mounting bracket

Display type: 4 digit 7-segment LED display

Material: Metal

Dimensions: Width: 30 cm
Depth: 20 cm
Height: 31 cm

Weight: 3,50 kg

Noise classification: Class 2 (slight noise); class 2 (slight noise)

Power cord

Cable construction: 3 x 0,75 mm² H05VV-F

Cable length: Approx. 1,2 m

Mounting bracket

Diameter mounting holes: 3 x Ø11mm; 4 x Ø5mm

Material: Metal, 2 mm

Remote control

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page(s)
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Typ A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm
Weight:	2,25 kg
Noise classification:	Class 0 (no noise at all)