

## EUROLITE Set 2x LED KLS-180 + 2x LED WF-40 + DMX LED Color Chief Controller

2x Compact Light Set, 2x Projection effect for water reflections including DMX lighting desk

GTIN: 4026397578058



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Fixtures available for LED PC-Control 512; Light Captain; Light J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: On stand
- spotlight**
- 4 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)<BR>4 spots controlled separately
- bar**
- 4 LEDs 1 W SMD 8072 cold white (CW)<BR> LEDs controlled separately
- <p>EUROLITE LED WF-40 Water Effect
- <h2 class="featureSatz">Projection effect for water reflections, with RGBW color mixing & DMX</h2>Static and moving water effects with a 3D look in vibrant colors

### Logistic

EAN / GTIN: 4026397578058  
 Weight: 37,10 kg  
 Length: 1.26 m  
 Width: 0.52 m  
 Height: 0.67 m

- 1 LED 40 W COB (chip-on-board) 4in1 QCL RGBW
- Focus manual
- Dimmer electronic; color blend stepless; Rotation speed stepless; color change adjustable
- Beam effect; strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; stand-alone; master/slave function
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; decoration; restaurants, bars and hotels; mobile djs / entertainer
- Application possibility: Suspended; on stand
- <p>EUROLITE DMX LED Color Chief Controller
- <h2 class="featureSatz">DMX lighting desk with innovative control concept for LED spotlights</h2>Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

## Technical specifications:

---

Weight: 32.50 kg

---

### EUROLITE LED KLS-180 Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0.5 - 20 Hz

DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	9000 Hz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Attachment system:	Ø 35mm 1x mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Material:	Metal; plastic
Dimensions:	Width: 60.5 cm Depth: 14 cm Height: 23 cm
Weight:	4.85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
LED type:	4 x 1 W SMD 8072 cold white (CW)
Diameter mounting holes:	3 x Ø11mm; 2 x Ø3mm
Material:	Metal, 2 mm
Cable construction:	3 x 0.75 mm² H05VV-F
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE LED WF-40 Water Effect**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Device fuse:	5 x 20 mm, T 1 A fuse replaceable

Lamp type:	LED lamp
LED type:	1 x 40 W COB (chip-on-board) 4in1 QCL RGBW
Flash rate:	2.5 - 19 Hz
Equipment:	Focus manual
DMX channels:	9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; stand-alone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief
Beam angle (1/2 peak):	30°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 27.7 cm Depth: 25.2 cm Height: 18.7 cm
Weight:	3.32 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, 2 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE DMX LED Color Chief Controller**

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A

Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

---

### Scope of delivery:

---

#### **2 x EUROLITE LED KLS-180 Compact Light Set**

- 1 x spotlight
- 1 x power cord
- 1 x bag
- 1 x remote control
- 1 x battery
- 1 x user manual

#### **2 x EUROLITE LED WF-40 Water Effect**

- 1 x light effect
- 1 x power cord
- 1 x user manual

#### **1 x EUROLITE DMX LED Color Chief Controller**

- 1 x controller
- 1 x user manual
- 1 x external mains adapter