

OMNITRONIC Set UHF-201 Wireless Mic System + Bodypack 863.010 MHz Art. No.: 20000438



# The article is no longer in our assortment.

### Features:

## OMNITRONIC UHF-201 Wireless Mic System 863.010MHz

Wireless microphone system with UHF PLL technology

- Receiver unit and hand-held microphone with UHF PLL technology

Operation in the low-interference UHF band

- Parallel operation of up to 4 sets is possible without any interference
- Volume control
- XLR and 6.3 mm output
- Jack cable included
- LEDs for power, carrier and audio signal
- Microphone with mute switch and color indication
- Matching pocket transmitter can be ordered separately
- License-free and approved in the EU
- Polar pattern: Cardioid
- UHF 863 865 MHz License-free and approved in Europe **Package contents**
- 1 x microphone

# OMNITRONIC UHF-200 BP Bodypack 863.010MHz

Bodypack transmitter with lavalier microphone

- Pocket transmitter as UHF PLL system, matching receivers with the same carrier frequency
- Operation in the low-interference UHF band
- Incl. lavalier microphone
- Transmitting power 10 mW
- Sensitivity adjustable

Logistic

- Power LED
- Mute switch
- Operation via 2 x 1.5 V batteries, type AA
- License-free and approved in the EU
- Polar pattern: Cardioid
- UHF 863 865 MHz License-free and approved in Europe

## **Technical specifications:**

Weight:

0,83 kg

#### OMNITRONIC UHF-201 Wireless Mic System 863.010MHz

Туре:	Wireless set
Power consumption:	10,00 W
Capsule type:	Dynamic
Polar pattern:	Cardioid
Frequency range:	40 - 18000 Hz
Frequency band:	UHF 863 - 865 MHz
Frequency selection:	Fixed frequencies
Dimensions:	Width: 21 cm Depth: 4,5 cm Height: 15,5 cm
Weight:	0,72 kg
Battery:	2 x Mignon (AA) (not included)
System:	Non-Diversity
Carrier frequency:	863.010 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Audio outputs:	400 mV, 2.2 kohms (XLR, bal.)
	200 mV, 2.2 kohms (6.3 mm jack, unbal.)
Power supply	
Receiver:	100-240 V AC, 50/60 Hz via supplied power unit
Dimensions, weight:	
Receiver:	155 x 210 x 45 mm (W x D x H), 1 kg
Microphone:	50 x 265 mm (D x L), 280 g

## OMNITRONIC UHF-200 BP Bodypack 863.010MHz

	ne
Capsule type: Condenser	

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Frequency range:	40 - 18000 Hz
Frequency band:	UHF 863 - 865 MHz
Frequency selection:	Fixed frequencies
Switch:	On/off switch; mute control
Dimensions:	Width: 65 cm
	Depth: 20 cm
	Height: 2,5 cm
Weight:	0,12 kg
Carrier frequency:	863.010 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Connection:	3.5 mm jack