

## EUROLITE Set 4x AKKU Flat Light 1 black + Case + Charger

4x flat spotlight with 15 W RGBW LED, flightcase and charger

Art. No.: 20000442

GTIN:



**The article is no longer in our assortment.**

### Features:

#### EUROLITE AKKU Flat Light 1 bl

Flat spotlight with 15 W RGBW LED, QuickDMX transceiver and bracket

- With QuickDMX transceiver - cordless, flexible and versatile
- Equipped with a 15 W QCL LED in red, green, blue and white
- Cordless and versatile
- Elegant housing for indoor use
- With integrated QuickDMX transmitter/receiver for the wireless transmission of DMX512 signals
- Operation via built-in rechargeable lithium-ion battery with up to 18 hours operating time
- Integrated automatic charging of the battery with indicator
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Addressing and setting via Control Board with touch buttons and LCD
- Inclination angle manually adjustable via the bracket
- Charger included in delivery
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via Master/slave function; stand-alone; QuickDMX; IR remote control
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 8°
- For application areas such as: Wedding/gala/events; small rental
- Silent operation
- device**
- Cordless, flexible and versatile

### Logistic

- Battery operation up to 18h depending on program used

**Package contents**

- 1 x remote control, 1 x device, 1 x user manual, 1 x external mains adapter

**ROADINGER Flightcase 4x AKKU Flat Light Series**

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

**EUROLITE Charger 4x Akku Flat Light Series**

Power supply with cable for simultaneous charging of 4 x Akku Flat Light 1/3

- 1 x charger, 1 x power cord, 1 x adapter cable

**Technical specifications:**

---

Weight: 11,32 kg

---

**EUROLITE AKKU Flat Light 1 bl**

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2,5 A
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Lamp type:	LED lamp
LED:	1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; stand-alone; QuickDMX; IR remote control
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Black
Dimensions:	Width: 16,8 cm Depth: 13,8 cm Height: 6,2 cm

Weight:	1,67 kg
Noise classification:	Class 0 (no noise at all)
Device	
Battery pack type:	1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x AKKU Flat Light Series**

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	7 cm x 18,5 cm x 9 cm
Accessory compartment:	38 cm x 6,5 cm x 12 cm
Inside dimensions:	38 cm x 25 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4,15 kg

#### **EUROLITE Charger 4x Akku Flat Light Series**

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 6 A
Power connection:	Mains input power supply cord with Euro plug (provided)
Power output:	4 x Coaxial power connector (F)
Weight:	490 g