

## EUROLITE Set Flightcase 4x AKKU Flat Light 1 + Charger

Carrying case, PRO version

Art. No.: 20000448

GTIN:



**List price: 355.81 €**

incl. 19% VAT.

### Features:

Carrying case, PRO version

- ,

### Logistic

#### ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3<p class='attributgroup'>Package contents

- 1 x charger, 1 x power cord, 1 x adapter cable

## Technical specifications:

---

|         |         |
|---------|---------|
| Weight: | 4,64 kg |
|---------|---------|

---

### ROADINGER Flightcase 4x AKKU Flat Light Series

|                          |   |
|--------------------------|---|
| Aluminum profile frames: | 25 mm   |
| Carrying handle:         | 1 pc/pcs                                      |
| Lock:                    | Butterfly lock: 1 pc/pcs                      |
| Use of brands:           | Branded hardware                              |
| Material:                | Birch multiplex, 7 mm                         |
| Color:                   | Dark brown, laminated                         |
| Device compartment:      | 8 cm x 19 cm x 10 cm                          |
| Accessory compartment:   | 38 cm x 6,5 cm x 12 cm                        |
| Inside dimensions:       | 38 cm x 27 cm x 12 cm                         |
| Dimensions:              | Width: 42 cm<br>Depth: 31 cm<br>Height: 20 cm |
| Weight:                  | 4,15 kg                                       |

### EUROLITE Charger 4x Akku Flat Light Series

|                   |  |
|-------------------|--|
| Power supply:     | 100-240 V AC, 50/60 Hz<br>12,6V DC 6000 mA   |
| Power connection: | Mains input via C8 (M) "figure 8" mounting<br>version power supply cord with Euro plug<br>(provided) |
| Power output:     | 4 x coaxial power connector (F)  |
| Weight:           | 0,49 kg  |