

EUROLITE Set 4x AKKU UP-1 Glow QCL + Case with charging function

Art. No.: 20000459

4x LED uplight with 15 W 4in1 LED including PRO flightcase with charging function

GTIN:



The article is no longer in our assortment.

Features:

Logistic

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

LED Uplight with 15 W 4in1 LED, tiltable head, QuickDMX & mood light

- Integrated QuickDMX transceiver for wireless DMX control
- Milky front screen provides a pleasantly soft light with RGBW color mixing
- Interchangeable front lens for 9° or 15° beam angle
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Integrated automatic charging of the battery with indicator
- Cordless, flexible and versatile
- Battery operation up to 24h depending on program used
- 30 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 1 powerful LED 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control; master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- With a KENSINGTON LOCK theft protection
- Silent operation
- For application areas such as: Small rental; wedding/gala/events

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x lens, 1 x user manual

ROADINGER Flightcase 4x AKKU UP-4 QuickDMX with charging function

Trunk case with castors

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 8 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Battery pack:	Battery operation up to 24h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	30 x 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 1 x 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control; master/slave function
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9° 15°
Beam angle (1/10 peak):	18° 30°

Housing color:	Black
Attachment system:	Mounting bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 13,8 cm Depth: 13,8 cm Height: 20 cm
Weight:	2,90 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU UP-4 QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 8 mm
Color:	Black, laminated
Device compartment:	18 cm x 19,5 cm x 17 cm
Accessory compartment:	9,5 cm x 41 cm x 17 cm
Inside dimensions:	49,5 cm x 41 cm x 17 cm
Dimensions:	Width: 62 cm Depth: 46 cm Height: 40,5 cm
Weight:	14,65 kg