

EUROLITE Set LED SL-400 DMX + STV-200

Follow spot with 300 W warm white LED including follow spot stand PRO version

Art. No.: 20000479

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED SL-400 DMX Search Light

Follow spot with warm white 300 W LED for medium distances, zoom, CRI >80

- Manual control via control panel with buttons and faders
- 1 powerful LED 300 W COB (chip-on-board) warm white (WW)
- Focus manual; Iris stepless
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- With a beam angle of 7° - 17°
- Good color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- Direct color temperature selection for 4 preset values
- Dimmer electronic
- Strobe effect
- Suitable for a range of use from 25 to 50 meters
- Color wheel with 5 dichroic filters plus open
half colors selectable
- Preprogrammed in LED PC-Control 512; Light Captain
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; Stage; theater; Rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x mounting bracket, 1 x hex key

EUROLITE STV-200 Follow Spot Stand, Stainless Steel

PRO version with ball bearing head, maximum load 50 kg, maximum height 160 cm

Logistic

- Professional follow stand for mobile lighting systems
- Stand head lies on a ball-bearing
- Heavy-duty stainless steel version for extra stability and safety
- Easy handling
- Safety ring for height adjustment
- Adjustable height

Technical specifications:

Weight: 17,80 kg

EUROLITE LED SL-400 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	1 x 300 W COB (chip-on-board) warm white (WW)
Color temperature:	3500K
Flash rate:	1 - 20 Hz
Equipment:	Focus manual; Iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	7° - 17°
Beam angle (1/2 peak):	7 - 13°
Beam angle (1/10 peak):	3 - 17°
Color rendering index (CRI):	80 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Range of use:	25m - 50m
Dimensions:	Length: 77 cm Width: 27 cm Height: 29 cm
Weight:	11,50 kg
Noise classification:	Class 2 (slight noise)

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE STV-200 Follow Spot Stand, Stainless Steel

Maximum carrying capacity: 50 kg

Height: Maximum: 160 cm
Minimum: 110 cm

Attachment system: M12 thread

Type (general stands): Light stand/manual

Material: Aluminum; stainless steel

Color: Silver

Weight: 6,30 kg
