

EUROLITE Set LED SL-160 + Case

Follow spot with cold white 160 W LED including PRO flightcase

Art. No.: 20000481

GTIN:



List price: 1783.81 €

incl. 19% VAT.

Features:

EUROLITE LED SL-160 Search Light

Follow spot with cold white 160 W LED for small to medium distances

- Comfortable control via control panel with buttons and faders
- 1 powerful LED 160 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- Dimmer electronic; CTO correction filter adjustable
- Strobe effect
- Color wheel with 5 dichroic filters plus open
- The device is cooled by cooling fan
- Control via stand-alone
- With a beam angle of 10°
- With mounting bracket
- Suitable for a range of use from to 20 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x mounting bracket, 1 x hex key

Logistic

ROADINGER Flightcase SL-160/SL-350

Trunk case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles

- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	19,05 kg
---------	----------

EUROLITE LED SL-160 Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 160 W COB (chip-on-board) cold white (CW)
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open
Cooling:	Cooling fan
Control:	Stand-alone
Beam angle:	10°
Beam angle (1/2 peak):	10°
Color temperature:	3200K; 4500K; 5600K
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting; metal
Range of use:	- 20m
Dimensions:	Length: 60 cm Width: 27,5 cm Height: 31,5 cm
Weight:	9,85 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 1,5 mm² H05VV-F
Cable length:	Approx. 1,4 m
Mounting bracket	
Diameter mounting holes:	3 x Ø13mm; 2 x Ø16mm
Material:	Aluminum casting, 4 mm
Color:	Black, matte
Hex key	
Material:	Steel

Color:	Silver
Dimensions:	Length: 8,5 cm Width: 0,6 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase SL-160/SL-350

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; plywood multi-layer glued
Color:	Dark brown, laminated
Device compartment:	61 cm x 19,5 cm x 25 cm
Inside dimensions:	68 cm x 34 cm x 29 cm
Dimensions:	Width: 72 cm Depth: 38 cm Height: 34,5 cm
Weight:	9,20 kg