EUROLITE Set 4x DMH-80 LED Spot + Case

4x PRO Moving Head with 75 W LED including PRO flightcase

Art. No.: 20000491

GTIN:

The article is no longer in our assortment.

Features:

FUTURELIGHT DMH-80 LED Spot

PRO moving-head with 75 W LED and unique 16-facet prism

- High PAN/TILT speed
- Number of scenes can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- 1 powerful LED 75 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 270° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; Prism 16-fold rotating; Focus motor-driven
- Gobo effect; beam effect; Strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; Sound to light via Microphone
- With a beam angle of 10° - 16°
- Multicolor LCD display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; Light Captain
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; Stage

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x xLR cable, 1 x omega bracket

ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130

PRO flightcase for 4 x PLB-130

- With 4 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT DMH-80 LED Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; Prism 16-fold rotating; Focus motor-driven
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 24mm Image diameter 19mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	11; 13; 17; 18
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control:	Stand-alone; DMX; RDM; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	10° - 16°
Beam angle (1/2 peak):	10 - 16°
Beam angle (1/10 peak):	10 - 16°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 8334 lx, 6m: 2169 lx Wide cold white (CW) 3m: 5211 lx, 6m: 1339 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 29,9 cm Depth: 25,2 cm Height: 39,8 cm
Weight:	9,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10 cm x 45 cm x 38,5 cm
Inside dimensions:	77 cm x 45 cm x 40,5 cm
Device compartment:	31,5 cm x 21,5 cm x 38,5 cm
Dimensions:	Width: 81 cm Depth: 50 cm Height: 43 cm
Weight:	22,60 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.