

EUROLITE Party-Accu-Camping Set

Battery powered party set with portable PA system and 3 lighting effects

Art. No.: 20000498

GTIN:



The article is no longer in our assortment.

Features:

- Portable all-in-one PA system with 40 watts output power
- 4-channel mixer
- 2-way bass-reflex system
- SD card slot and USB port
- 1 microphone input (XLR) with adjustable reverb effect
- UHF receiver unit and matching wireless microphone
- Power-efficient and battery-saving class D amplifier
- Tone control and master control
- Integrated automatic charging of the battery
- The device is cooled by passive convection cooling
- UHF 863 - 865 MHz License-free and approved in Europe
- Black metal grille
- Rugged carrying handle
- For application areas such as: Theater; mobile use; wedding/gala/events; product presentations and lectures

battery pack

- Battery pack must be ordered separately
- Cordless, flexible and versatile
- Battery operation up to 4h

audio player

- Control via Bluetooth; IR remote control
- Bluetooth: operating range up to 10m
- 2.4 GHz license-free worldwide
- 4 digit 7-segment LED display

microphone

- Polar pattern: Cardioid

Logistic

- Operating range up to 30m
- remote control**
- Operating range up to 10m
- <p>EUROLITE AKKU Mini PARty RGBW Spot
- <h2 class="featureSatz">DMX spotlight with 12 x 1 W LED in the colors red, green, blue and white</h2>Equipped with twelve 1 W LEDs - 3 x red, 3 x green, 3 x blue and 3 x white
- Small and compact, easy to transport, ideal for mobile use
- Operation via built-in rechargeable lithium-ion battery with min. 3 hours operating time
- Built-in auto and music show programs
- Functions: static colors, RGBW color mixture, internal programs, color change with diverse settings, dimmer and strobe settings
- Addressing via control panel with 4-digit LED display
- Additional controlling possibility via EUROLITE IR-25 remote control; included in delivery
- Built-in charging function via included USB charger
- Can also be charged via USB power banks
- Mounting bracket for ceiling or wall mounting
- Additional bracket for floor use
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LEDs 1 W SMD 8072 R/G/B/W (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- With a beam angle of 12°
- 4 digit 7-segment LED display
- For application areas such as: Gift idea

device

- Cordless, flexible and versatile
- Battery operation up to 3h depending on program used
- <p>EUROLITE AKKU BEL-15 Beam tc
- <h2 class="featureSatz">Handy battery-powered beam effect with up to 5 beams, transparent housing</h2>Powerful battery-powered beam effect in a pocket housing
- Cordless, flexible and versatile
- Battery operation up to 4h
- 5 LEDs 3 W high-power R/G/B/W/A
- Color change adjustable; color fade adjustable
- Multi beam effect; strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; sound to light via microphone
- With mounting bracket
- <p>EUROLITE AKKU BEK-10 Kaleidoscope tc
- <h2 class="featureSatz">Handy battery-powered kaleidoscope effect, transparent housing</h2>Powerful battery-powered Kaleidoscope Effect in a pocket housing
- Equipped with one bright 4in1 LED with 10 W in the colors red, green, blue, white
- Ideal for mobile use thanks to quick setup and rechargeable lithium-ion battery pack (up to 4 hours operating time)
- Transparent white plastic housing with plastic bracket
- Functions: Auto mode, automatic color change, fading colors, strobe effect
- Charger included in delivery
- Switch-mode power supply for operation between 100 and 240 volts
- 1 LED 10 W high-power 4in1 RGBW
- Flower effect; gobo effect
- The device is cooled by passive convection cooling
- Control via IR remote control; sound to light via microphone

device

- Cordless, flexible and versatile
- Battery operation up to 4h depending on program used

Technical specifications:

Weight:

6.70 kg

OMNITRONIC WAMS-65BT Wireless PA System

Power supply:	100-240 V AC, 50/60 Hz Or 12V DC
Power consumption:	60 W
Protection class:	Protection class I
Output power:	40 W RMS
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack (not included)
Frequency range:	62 - 18000 Hz
THD:	<0.5 % at 1 kHz
Cooling:	Passive convection cooling
Frequency band:	UHF 863 - 865 MHz
Carrier frequency:	865 MHz
Frequency stability:	± 0.005 %
Frequency selection:	Fixed frequencies
Housing color:	Black
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D
Control elements:	Echo effect control, audio player
Status LED:	Power, peak, ON AIR, signal, charge status indicator
Connections:	Input: microphone via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 6.3 mm plug (unbal.)
Channels:	Microphone channel: 1 x mono via XLR, channel control via rotary dial Input channel: 1 x stereo via RCA, channel control via rotary dial Input channel: 1 x stereo via audio player, channel control via rotary dial Input channel: 1 x mono via radio, channel control via rotary dial Master output: 1 x mono, channel control via rotary dial, tone control EQ
Speaker:	1 x woofer 6.5" 1 x tweeter 1"
Type of speaker:	Compact cabinet speaker; wireless PA system
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black
Dimensions:	Width: 23.5 cm Depth: 22 cm Height: 35 cm
Weight:	4.15 kg

Power supply:	3V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m
RF power output:	10 mW
Modulation:	FM
Switch:	On/off/mute switch
Material:	Plastic
Dimensions:	Length: 26 cm Diameter: Ø 4 cm
Weight:	0.115 kg
Control:	Bluetooth; IR remote control
Bluetooth device name:	Omnitronic
Audio player:	USB + SD + Bluetooth
Range:	Bluetooth: range up to 10m
Frequency band:	2.4 GHz
Display type:	4 digit 7-segment LED display
Music format:	MP3, WAV
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Power supply:	3V DC
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Range:	Range up to 10m
Battery pack type:	1 x lead 12 V, 2900 mAh,
Battery pack:	Battery operation up to 4h Recharging time 4h

Akku 12V/2900mAh WAMS-05 / WAMS-65

Weight:	1.094 kg
---------	----------

EUROLITE AKKU Mini PARTy RGBW Spot

Power supply:	5V DC
Power consumption:	10 W
Power connection:	Battery/battery pack Mains input via micro USB (F) mounting version power supply cord with AC adapter (provided)
Lamp type:	LED lamp
LED type:	12 x 1 W SMD 8072 R/G/B/W (homogenous color mix)
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	27°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 16.2 cm Depth: 11.7 cm Height: 13.3 cm
Weight:	0.60 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Battery pack type:	1 x lithium ion 3.7 V, 2000 mAh, 7.4 Wh
Battery pack:	Battery operation up to 3h depending on program used Recharging time 3h
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE AKKU BEL-15 Beam tc

Power supply:	100-240 V AC, 50/60 Hz 3.7V DC 2200 mA
Power consumption:	9.2 W
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	1 x lithium ion 3.7 V, 2200 mAh, 8 Wh
Battery pack:	Battery operation up to 4h Recharging time 4.5h
Lamp type:	LED lamp
LED type:	5 x 3 W high-power R/G/B/W/A
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; sound to light via microphone
Housing color:	Clear
Attachment system:	Mounting bracket
Dimensions:	Width: 14.6 cm Depth: 15.5 cm Height: 15 cm
Weight:	0.39 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE AKKU BEK-10 Kaleidoscope tc

Power supply:	100-240 V AC, 50/60 Hz 3.7V AC 2200 mA
Pin configuration:	Inside + / outside -
Power consumption:	9.2 W
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Lamp type:	LED lamp
LED type:	1 x 10 W high-power 4in1 RGBW
Cooling:	Passive convection cooling
Control:	IR remote control; sound to light via microphone
Housing color:	Clear
Dimensions:	Width: 14.6 cm Depth: 15.5 cm Height: 11.5 cm
Weight:	0.46 kg
Battery pack type:	1 x lithium ion 3.7 V, 2200 mAh, 8 Wh
Battery pack:	Battery operation up to 4h depending on program used Recharging time 4.5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x OMNITRONIC WAMS-65BT Wireless PA System

1 x device
1 x power cord
1 x microphone
1 x remote control
1 x user manual
1 x declaration of conformity

1 x Akku 12V/2900mAh WAMS-05 / WAMS-65

1 x device

1 x EUROLITE AKKU Mini PARTY RGBW Spot

1 x spotlight
1 x user manual
1 x external mains adapter
1 x remote control
1 x battery

1 x EUROLITE AKKU BEL-15 Beam tc

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x user manual

1 x EUROLITE AKKU BEK-10 Kaleidoscope tc

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x user manual