



The article is no longer in our assortment.

Features:

EUROLITE LED KLS-401 Compact Light Set

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 180 x 10 mm LED per spot (60 x red, 60 x green, 60 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 180 powerful LEDs 10 mm R/G/B-
 spots controlled separately
- Control via stand-alone; DMX; Foot switch (optional); IR remote control (optional)

Logistic

- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x spotlight

EUROLITE STV-50-WOT EU Steel stand

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Made in Europe

Package contents

- 1 x user manual

Technical specifications:

Weight: 14,80 kg

EUROLITE LED KLS-401 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	180 x 10 mm R/G/B
DMX channels:	15
Control:	Stand-alone; DMX; Foot switch (optional); IR remote control (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Dimensions:	Width: 1,2 m Depth: 5,5 cm Height: 31 cm
Weight:	9,30 kg
DMX connection:	3-pin XLR
LED type:	10 mm
LED number:	720 (240 red, 240 green, 240 blue)
TV spigot:	D = 28 mm
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE STV-50-WOT EU Steel stand

Maximum carrying capacity:	30 kg
Height:	Maximum: 315 cm Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm (short)
Type (general stands):	Light stand/manual
Material:	Steel (powder-coated); Steel/magnesium
Color:	Black
Weight:	5,50 kg