

## OMNITRONIC PA Set AZX active M

2x AZX-115A PA Subwoofer active 400W, 2x AZX-212A 2-Way Top active 250W and 2x Distance Tube

Art. No.: 2000527

GTIN:



**List price: 1890.91 €**

incl. 19% VAT.

### Features:

#### OMNITRONIC AZX-115A PA Subwoofer active 400W

Active 15" PA bassreflex subwoofer, 400 W RMS

- 38 cm (15") bass speaker with 63 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Rugged carrying handle
- Black metal grille with acoustic foam
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; Rental

#### Package contents

- 1 x bass, 1 x user manual, 1 x power cord

#### OMNITRONIC AZX-212A 2-Way Top active 250W

Active speaker with 12" woofer, 1,35" driver, LF: 200 W RMS, HF: 50 W RMS

- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- Balanced signal input XLR/6.3 mm jack, switchable mic/line
- HF adjustment -4 dB, -2 dB, 0 dB
- Black metal grille with acoustic foam
- Rugged carrying handle
- Application possibility: Standing; suspended; monitoring; on stand
- With rigging points
- Dual flange

### Logistic

- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; Rental

**Package contents**

- 1 x user manual, 1 x power cord, 1 x compact cabinet speaker

**OMNITRONIC Distance Tube Subwoofer/Satellite M20**

Variable distance tube, M20 thread, height adjustable 75-130 cm, max. load 30 kg

- Connecting tube for satellite systems
- Locking screw and bolt
- Powder-coated steel version
- Adjustable height
- M20 thread

**Package contents**

- 1 x distance tube, 1 x user manual

**Technical specifications:**

---

Weight: 92,40 kg

---

**OMNITRONIC AZX-115A PA Subwoofer active 400W**

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 400W RMS
Frequency range:	40 - 250 Hz
Sensitivity:	94 dB (1W/1m)
Attachment system:	M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 15" Basket material: Steel Voice coil lows 2,5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	MDF (Medium-density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 53 cm

Depth: 55 cm

Height: 47 cm

---

Weight: 26,15 kg

---

#### **OMNITRONIC AZX-212A 2-Way Top active 250W**

Power supply: 230 V AC, 50 Hz

---

Power consumption: 650 W

---

Protection class: Protection class I

---

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

---

Power: Rated: 200W RMS LF  
Rated: 50W RMS HF

---

Frequency range: 55 - 20000 Hz

---

Sensitivity: 95 dB (1W/1m)

---

Attachment system: Dual flange: Ø 35mm (0°/5°)

---

Flying points: 7 x M10 thread

---

Circuitry: Class D Biamp

---

Control elements: Power switch, Input sensitivity switch, tone control, level control

---

Controls: Limiter

---

Status LED: Limit, power, signal

---

Connections: Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)  
Output: line via 1 x 3-pin XLR

---

Input channels: 1 x mono with Mic-line switch via Combination socket (XLR/jack), channel control via Rotary dial

---

Equalizer: Master: 1 x 2-band tone control

---

Speaker: Woofer 12" with ferrit magnet  
Basket material: Steel  
Conematerial: Cardboard/paper  
Voice coil lows 2"  
Voice coil compression tweeter highs 1,35"

---

Type of speaker: Compact cabinet speaker

---

Carrying handle: 1 pc/pcs

---

Material: MDF (Medium-density fiberboard), 15 mm

---

Color: Black, textured coating, painted

---

Dimensions: Width: 37 cm  
Depth: 35,2 cm  
Height: 62,2 cm

---

Weight: 19,15 kg

---

#### **OMNITRONIC Distance Tube Subwoofer/Satellite M20**

Maximum carrying capacity: 30 kg

---

Tube diameter sector: 41 - 35 mm

---

Height: Maximum: 130 cm

	Minimum: 75 cm
Attachment system:	Ø 35mm
Type (general stands):	Distance tube
Color:	Black
Thread:	M20 thread
Weight:	900 g