

OMNITRONIC Set BOB-10A bk + 2x BOB-4 bk

BOB-10A Subwoofer active including 2 x 4" satellite speakers BOB-4

Art. No.: 20000532

GTIN:



List price: 641.41 €

incl. 19% VAT.

Features:

OMNITRONIC BOB-10A Subwoofer active black

10" subwoofer with DSP and Bluetooth for the BOB series

- 10" bassreflex subwoofer with DSP and 900 watts RMS power
- Flexibly extendable with BOB-4 satellites for 2.1, 4.1 and 8.1 configurations
- DSP-controlled class D amplifier (300 W + 2 x 300 W)
- Signal inputs via combo jacks (XLR/6.3 mm jack) and RCA
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- Control via Bluetooth
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- 4 Rugged carrying handles
- DSP presets: FLAT; DJ; LIVE; SPEECH

Package contents

- 1 x bass, 1 x user manual, 1 x power cord, 2 x speaker cable, 4 x foot, 4 x screw, 1 x declaration of conformity

Logistic

OMNITRONIC BOB-4 Top 16 Ohm black 2x

2 x 4" satellite speakers with bracket for the BOB series

- 16-ohm speaker pair with 4" full-range speaker
- For use with BOB-10A subwoofers for 2.1, 4.1 and 8.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers

- With Mounting bracket
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Package contents

- 2 x top, 4 x knurled screw, 2 x mounting bracket, 2 x plug (male)

Technical specifications:

Weight: 21,50 kg

OMNITRONIC BOB-10A Subwoofer active black

| | |
|-----------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 1060 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power: | Rated: 1x 300W RMS LF Rated: 2x 300W RMS HF |
| Frequency range: | 45 - 250 Hz |
| Sensitivity: | 100 dB |
| Max. SPL: | 125 dB |
| DSP: | Digital signal processor |
| DSP presets: | FLAT; DJ; LIVE; SPEECH |
| Control: | Bluetooth |
| Attachment system: | 2x M20 thread |
| Circuitry: | Class D |
| Control elements: | Phase reversal switch |
| Controls: | Softstart; short-circuit; limiter; Overvoltage; overheat; limiter |
| Status LED: | Signal, power, limit, fault, DSP presets |
| Connections: | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: speaker via 2 x speaker built-in socket (F) Output: line via 2 x 3-pin XLR |
| Input channels: | 1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial |
| Speaker: | 1 x woofer 10" Voice coil lows 2" |
| Type of speaker: | Subwoofer |
| Type of construction: | Vented |
| Carrying handle: | 4 pc/pcs |
| Material: | MDF (Medium-density fiberboard), 15 mm |
| Color: | Black, textured coating |
| Dimensions: | Width: 30 cm Depth: 47 cm |

| | |
|---------|---------------|
| | Height: 43 cm |
| Weight: | 17,50 kg |

OMNITRONIC BOB-4 Top 16 Ohm black 2x

| | |
|--------------------|--|
| Power: | Program: 150W Rated: 75W RMS |
| Frequency range: | 150 - 16000 Hz |
| Sensitivity: | 90 dB (1W/1m) |
| Max. SPL: | 109 dB |
| Impedance: | 16 ohms |
| Attachment system: | Mounting bracket |
| Connections: | Input: speaker via 1 x screw plug-in terminal Input: speaker via 1 x speaker built-in socket (F) |
| Speaker: | 1 x compression tweeter highs 4" Basket material: Steel Conematerial: Cardboard/paper 1 x Voice coil compression tweeter highs 1" |
| Material: | ABS Acrylonitrile butadiene styrene |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 15 cm Depth: 16 cm Height: 15,8 cm |
| Weight: | 4,00 kg |