

EUROLITE Set 4x LED Umbrella 95 + Case

4x LED Umbrella 95 including flightcase with castors

Art. No.: 20000542

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED Umbrella 95

Extraordinary RGB eye-catcher

- 114 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
7 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- Easy to assemble
- 3 digit 7-segment LED display
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; clubs/dancing school; restaurants, bars and hotels; stage
- Application possibility: Suspended; on stand

Package contents

- 1 x omega bracket, 1 x device, 1 x user manual, 1 x power cord, 1 x multipin cable, 1 x umbrella

Logistic

ROADINGER Flightcase 4x LED Umbrella

Trunk case with castors

- With 4 device compartments

- High-quality workmanship with plywood multi-layer glued 7 mm, red, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 29,22 kg |
|---------|----------|

EUROLITE LED Umbrella 95

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 10 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| LED type: | 114 x SMD 5050 3in1 TCL RGB (homogenous color mix) |
| DMX channels: | 6; 24 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Setup: | Easy to assemble |
| Housing color: | Black |
| Display type: | 3 digit 7-segment LED display |
| Weight: | 2,68 kg |
| Dimensions: | Diameter: Ø 95 cm |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED Umbrella

| | |
|--------------------------|----------|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |

| | |
|------------------------|---|
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Red, laminated |
| Accessory compartment: | 98,5 cm x 12,5 cm x 20 cm |
| Device compartment: | 18,5 cm x 24 cm x 20 cm |
| Inside dimensions: | 92,5 cm x 36,5 cm x 20 cm |
| Dimensions: | Width: 104 cm Depth: 43 cm Height: 41 cm |
| Weight: | 18,50 kg |