

FUTURELIGHT Set 2x DMH-300 CMY Moving-Head + Case

2x PRO beam/wash Moving Head with 270 W COB LED including flightcase with wheels

Art. No.: 20000543

GTIN:







List price: 8566.81 €

incl. 19% VAT.

Features: Logistic

2x PRO beam/wash Moving Head with 270 W COB LED including flightcase with wheels

- Positioning within PAN and TILT

FUTURELIGHT DMH-300 CMY Moving Head

PRO beam/wash moving-head with 270 W COB LED, large zoom and CMY color mixing

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 1 powerful LED 270 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 265° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; Prism 3-fold rotating; Zoom motor-driven; Focus motor-driven; frost filter stepless; Iris; Iris stepless
- Gobo effect; beam effect; Strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- The device is cooled by temperature-controlled fan

- Control via stand-alone; DMX; RDM; Sound to light via Microphone
- Flicker-free
- With a beam angle of 8° 44°
- LCD display
- Dimmer electronic; pulse-width modulation adjustable
- CMY+CTO color mixing for indefinite color variations
- Preprogrammed in Light Captain
- For application areas such as: Wedding/gala/events; Stage; theater; Rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x xLR cable, 1 x plate

ROADINGER Flightcase 2x DMH-300 LED

Trunk case with castors, PRO version

- With accessory compartment
- With 2 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELICHT DMU 200 CMV Maving Hood

FUTURELIGHT DMH-300 CMY Moving Head	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	340 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	1 x 270 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	265° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; Prism 3-fold rotating; Zoom motor-driven; Focus motor-driven; frost filter stepless; Iris; Iris stepless
Color generation:	CMY+CTO color mixing for indefinite color variations
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect Gobo wheel with rotating gobos, 7 gobos and open

	Outside diameter 27mm
	Image diameter 22mm
	Shake effect
	Gobos changeable
DMX channels:	Slot-in gobo system for easy gobo replacement 19; 21; 28; 29
DMX input:	1 x 3-pin XLR (M) mounting version
	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; Sound to light via Microphone
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 44°
Beam angle (1/2 peak):	8 - 44°
Beam angle (1/10 peak):	8 - 44°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 58069 lx, 6m: 12229 lx
	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx
Housing color:	
Housing color: Display type:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx
	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black
Display type:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display
Display type:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm
Display type:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm Depth: 36,9 cm
Display type: Dimensions:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm Depth: 36,9 cm Height: 53,4 cm
Display type: Dimensions: Weight:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm Depth: 36,9 cm Height: 53,4 cm 25,10 kg
Display type: Dimensions: Weight: Noise classification:	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm Depth: 36,9 cm Height: 53,4 cm 25,10 kg
Display type: Dimensions: Weight: Noise classification: Legal specifications	Wide cold white (CW) 3m: 2745 lx, 6m: 736 lx Black LCD display Width: 44,5 cm Depth: 36,9 cm Height: 53,4 cm 25,10 kg Class 2 (slight noise)

ROADINGER Flightcase 2x DMH-300 LED

9	
Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	32,5 cm x 42,5 cm x 47 cm
Accessory compartment:	21 cm x 42,5 cm x 34,5 cm
Inside dimensions:	86 cm x 42,5 cm x 47 cm
Dimensions:	Width: 93,5 cm
	Depth: 46,5 cm

Height: 94 cm
36,10 kg

Weight: