

The article is no longer in our assortment.

Features:

- For application areas such as: Carnival
- TCM FX E-Shot
- Electric firing unit for confetti and streamers
- The electric shooter can be used for confetti or streamer cannons
- Suitable for electric cannons with 50and 80 cm length
- The shooting angle can be adjusted steplessly
- Activated by a 230V power source
- Output distance: Approx. 20 m
- Control via plug and play
- Made in Europe
- For application areas such as: Carnival **Package contents**
- 1 x device, 1 x user manual
- PSSO PowerCon Power Cable 3x1.5 1.5m H07RN-F
- Built with NEUTRIK connector
- Made in Europe
- Package contents
- 1 x power cord
- ROADINGER Flightcase 4x AKKU UP-4
- Trunk case, PRO version
- Cable bushing allows loading the devices inside
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle

Logistic

- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Rubber feet
- Branded hardware
- Made in Europe

- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 12,95 kg

TCM FX E-Shot

| Power supply: | 230 V AC, 50 Hz |
|--------------------|--|
| Power consumption: | 100 W |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug |
| Power output: | 1 x PowerCON (gray), mounting version 1 x special connector recessed mounting |
| Output distance: | Approx. 20 m |
| Control: | Plug and play |
| Housing color: | Black |
| Dimensions: | Width: 12 cm Depth: 13 cm Height: 16 cm |
| Weight: | 1,78 kg |
| | |

PSSO PowerCon Power Cable 3x1.5 1.5m H07RN-F

| Cable construction: | 3 x 1,5 mm ² H07RN-F |
|---------------------|---------------------------------|
| Cable length: | 1,5 m |
| Plug A: | 1 x safety plug (M) |
| Plug B: | 1 x PowerCON (blue) |
| Use of brands: | Built with NEUTRIK connector |
| Color: | Black |
| Weight: | 0,31 kg |

ROADINGER Flightcase 4x AKKU UP-4

| Maximum load: | 25 kg |
|--------------------------|--------------------------|
| Aluminum profile frames: | 25 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Transport aid: | Rubber feet |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Use of brands: | Branded hardware |
|-------------------------|-------------------------|
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Compartment dimensions: | 16 cm x 15 cm x 15,5 cm |
| Inside dimensions: | 33 cm x 31 cm x 15,5 cm |
| Dimensions: | Width: 37 cm |
| | Depth: 35 cm |
| | Height: 25,5 cm |
| Weight: | 4,59 kg |
| | |