

EUROLITE Set 2x LED PLL-360 6000K Panel + Case

2x surface light with 360 cold white LEDs and DMX including PRO flightcase

Art. No.: 2000601

GTIN:



List price: 1331.61 €

incl. 19% VAT.

Features:

EUROLITE LED PLL-360 6000K Panel

Surface light with 360 cold white (CW)LEDs and DMX

- 360 powerful LEDs 0,5 W SMD 2835 cold white (CW)
- Energy-saving, durable and environmentally friendly
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via Quick select potentiometer for brightness; DMX; Master/slave function
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display
- Slim, rugged metal housing
- For application areas such as: Video and photography; Stage; Trade fair and shop fitting; theater
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Various versions available
- Dimmable
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

Package contents

Logistic

- 1 x spotlight, 1 x user manual, 1 x power cord

ROADINGER Flightcase 2x LED PLL-360

Trunk case, PRO version

- With accessory compartment
- With 2 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 23,00 kg

EUROLITE LED PLL-360 6000K Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED:	360 x 0,5 W SMD 2835 cold white (CW)
Color temperature:	6000K
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness; DMX; Master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 498 lx, 6m: 148 lx
Lamp life:	50000 h
Luminous flux:	9937 lm

Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 57 cm Depth: 12 cm Height: 31 cm
Weight:	6,10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F

ROADINGER Flightcase 2x LED PLL-360

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Dark brown, laminated
Accessory compartment:	61 cm x 10,5 cm x 26 cm
Device compartment:	57 cm x 8 cm x 26 cm
Inside dimensions:	61 cm x 26 cm
Dimensions:	Width: 65 cm Depth: 37 cm Height: 48 cm
Weight:	10,80 kg