

EUROLITE Set 2x LED STP-10 Sunbar 3200K 10x5W Light Bar + Case

2x LED light bar with warm white beam effects including PRO flightcase

Art. No.: 20000615

GTIN:



List price: 772.31 €

incl. 19% VAT.

Features:

EUROLITE LED STP-10 Sunbar 3200K 10x5W Light Bar 6°

LED light bar with warm white beam effects and narrow beam angle

- 10 powerful LEDs 5 W SMD 3535 warm white (WW)
LEDs controlled separately
- CREE LED installed
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; master/slave function; stand-alone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With a beam angle of 6°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; installation; stage; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual, 1 x plug (male)

Logistic

ROADINGER Flightcase 2x LED STP-7

Carrying case, PRO version

- 6 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding

- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case

Technical specifications:

Weight:	17,30 kg
---------	----------

EUROLITE LED STP-10 Sunbar 3200K 10x5W Light Bar 6°

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	10 x 5 W SMD 3535 warm white (WW)
LED manufacturer:	CREE
Flash rate:	0 - 20 Hz
DMX channels:	1; 3; 5; 10; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; master/slave function; stand-alone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	6°
Beam angle (1/2 peak):	6°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 99,5 cm Depth: 15 cm Height: 80 cm
Weight:	3,90 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED STP-7

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Outer compartment:	100 cm x 5 cm x 15 cm
Inside dimensions:	100 cm x 25,5 cm x 15 cm
Middle compartment:	100 cm x 8,5 cm x 15 cm
Material thickness:	6 mm
Dimensions:	Length: 104 cm Width: 30 cm Depth: 22,5 cm
Weight:	9,50 kg