

# EUROLITE Set ML-300 ABL Spot + STV-200 Follow spot stand

Spotlight with halogen lamp and LED ambient illumination incl. PRO follow spot stand

Art. No.: 20000624









# The article is no longer in our assortment.

Features: Logistic

#### **EUROLITE ML-300 ABL Spot**

Midsize spotlight with halogen lamp and LED ambient illumination

- RGB LEDs are concealed under the mesh cover, in order to completely illuminate the large reflector with color
- When dimmed, the halogen lamp produces a wonderful, golden atmosphere light; when fully illuminated a bright, dazzling light
- Strobe effect with adjustable speed
- Various dimmer curves adjustable
- Mains input and output for power linking up to 8 units
- 18 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With mounting bracket
- LCD display

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

#### **EUROLITE STV-200 Follow Spot Stand, Stainless Steel**

PRO version with ball bearing head, maximum load 50 kg, maximum height 160 cm

- Professional follow stand for mobile lighting systems
- Stand head lies on a ball-bearing
- Heavy-duty stainless steel version for extra stability and safety

- Easy handling
- Safety ring for height adjustment
- Adjustable height

## **Technical specifications:**

Weight: 13,45 kg

### **EUROLITE ML-300 ABL Spot**

| version power sup (provided)  Power Output: PowerCON (gray)  Base: GY9.5  Lamp type: Halogen lamp  LED type: 18 x 0,2 W SMD 5  Flash rate: 0 - 20 Hz  DMX channels: 1; 2; 4; 7  DMX input: 1 x 3-pin XLR (M) 1 x 5-pin XLR (M) 1 x 5-pin XLR (M)  DMX output: 1 x 3-pin XLR (F)  Cooling: Passive convection  Control: Stand-alone; IR results of the converse |   |
|--|---|
| Suitable lamp:  Nominal wattage:  Power connection:  Mains input via Powers of version power supprovided)  Power output:  PowerCON (gray)  Base:  GY9.5  Lamp type:  Halogen lamp  LED type:  18 x 0,2 W SMD 5  Flash rate:  0 - 20 Hz  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M)  1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  Cooling:  Control:  Stand-alone; IR re  Preprogrammed in:  Housing color:  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg   |   |
| Nominal wattage:  Power connection:  Mains input via Powerson power sup (provided)  Power output:  PowerCON (gray)  Base:  GY9.5  Lamp type:  Halogen lamp  LED type:  18 x 0,2 W SMD 5  Flash rate:  0 - 20 Hz  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M)  1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR reflected by the convention of th |   |
| Power connection:  Mains input via Powerson power sup (provided)  Power output:  PowerCON (gray)  Base:  GY9.5  Lamp type:  Halogen lamp  LED type:  18 x 0,2 W SMD 5  Flash rate:  0 - 20 Hz  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M)  1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR result of the property  | 9.5   |
| version power sur (provided)  Power CON (gray)  Base: GY9.5  Lamp type: Halogen lamp  LED type: 18 x 0,2 W SMD 5  Flash rate: 0 - 20 Hz  DMX channels: 1; 2; 4; 7  DMX input: 1 x 3-pin XLR (M) 1 x 5-pin XLR (M) 1 x 5-pin XLR (M)  DMX output: 1 x 3-pin XLR (F)  Cooling: Passive convection  Control: Stand-alone; IR results of the conversion of the convers |   |
| Base: GY9.5  Lamp type: Halogen lamp  LED type: 18 x 0,2 W SMD 5  Flash rate: 0 - 20 Hz  DMX channels: 1; 2; 4; 7  DMX input: 1 x 3-pin XLR (M) 1 x 5-pin XLR (M) 1 x 5-pin XLR (F) 1 x 5-pin XLR (F)  Cooling: Passive convection  Control: Stand-alone; IR results of the preprogrammed in: Light'J; LED PC-Control: Silver  Attachment system: Mounting bracket  Display type: LCD display  Dimensions: Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight: 7,15 kg  | owerCON (blue), mounting pply cord with safety plug |
| Lamp type:  LED type:  18 x 0,2 W SMD 5  Flash rate:  0 - 20 Hz  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M)  1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  1 x 5-pin XLR (F)  1 x 5-pin XLR (F)  2 Cooling:  Passive convection  Control:  Stand-alone; IR reconstruction  Preprogrammed in:  Light'J; LED PC-Construction  Housing color:  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg   | )   |
| LED type:  Flash rate:  0 - 20 Hz  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M) 1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F) 1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR reconstruction  Preprogrammed in:  Light'J; LED PC-Construction  Housing color:  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm Depth: 27,5 cm Height: 45,5 cm  Weight:  7,15 kg   |   |
| Flash rate:  DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M)  1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR results and part of the properties of the propert |   |
| DMX channels:  1; 2; 4; 7  DMX input:  1 x 3-pin XLR (M) 1 x 5-pin XLR (M) 1 x 5-pin XLR (F) 1 x 5-pin XLR (F) 1 x 5-pin XLR (F) 2 Cooling:  Passive convection Control:  Stand-alone; IR result of the preprogrammed in:  Light'J; LED PC-Company Housing color:  Attachment system:  Mounting bracket Display type:  LCD display  Dimensions:  Width: 53 cm Depth: 27,5 cm Height: 45,5 cm Weight:  Weight:  7,15 kg   | 5050 3in1 TCL RGB                                   |
| DMX input:  1 x 3-pin XLR (M) 1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F) 1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR result in the preprogrammed in:  Light'J; LED PC-Cooling  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm Depth: 27,5 cm Height: 45,5 cm  Weight:  7,15 kg  |   |
| 1 x 5-pin XLR (M)  DMX output:  1 x 3-pin XLR (F)  1 x 5-pin XLR (F)  Cooling:  Passive convection  Control:  Stand-alone; IR results  Preprogrammed in:  Light'J; LED PC-Cooling  Housing color:  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg  |   |
| DMX output:  1 x 3-pin XLR (F) 1 x 5-pin XLR (F) Cooling: Passive convection Control: Stand-alone; IR response to the control of the control  | mounting version                                    |
| 1 x 5-pin XLR (F)  Cooling: Passive convection  Control: Stand-alone; IR results  Preprogrammed in: Light 'J; LED PC-0  Housing color: Silver  Attachment system: Mounting bracket  Display type: LCD display  Dimensions: Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight: 7,15 kg  | mounting version                                    |
| Cooling: Passive convector  Control: Stand-alone; IR re  Preprogrammed in: Light'J; LED PC-Cool  Housing color: Silver  Attachment system: Mounting bracket  Display type: LCD display  Dimensions: Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight: 7,15 kg   | mounting version                                    |
| Control: Stand-alone; IR respectively. Preprogrammed in: Light'J; LED PC-Control Silver  Housing color: Silver  Attachment system: Mounting bracket  Display type: LCD display  Dimensions: Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight: 7,15 kg   | mounting version                                    |
| Preprogrammed in:  Housing color:  Silver  Attachment system:  Mounting bracket  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg  | on cooling  |
| Housing color:  Attachment system:  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg   | emote control; DMX                                  |
| Attachment system:  Display type:  LCD display  Dimensions:  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg   | Control 512; Light Captain                          |
| Display type:  LCD display  Width: 53 cm  Depth: 27,5 cm  Height: 45,5 cm  Weight:  7,15 kg  |   |
| Dimensions:         Width: 53 cm           Depth: 27,5 cm         Height: 45,5 cm           Weight:         7,15 kg  |   |
| Depth: 27,5 cm Height: 45,5 cm  Weight: 7,15 kg  |   |
| Weight:         7,15 kg  |   |
| Weight: 7,15 kg  |   |
|  |   |
| Special product: Not designed for h  |   |
|  | household room illumination                         |
| Intended use: Show effect lighting   | ng  |

## **EUROLITE STV-200 Follow Spot Stand, Stainless Steel**

Maximum carrying capacity: 50 kg

Height: Maximum: 160 cm

Minimum: 110 cm

| Attachment system:     | M12 thread                |
|------------------------|---------------------------|
| Type (general stands): | Light stand/manual        |
| Material:              | Aluminum; stainless steel |
| Color:                 | Silver                    |
| Weight:                | 6,30 kg                   |