

EUROLITE Set 4x LED SLS-6 TCL Spot + Case TDV-1

4x flat spotlight with 6 x 8 W 3in1 LED with RGB including case

Art. No.: 20000632

GTIN:



List price: 355.81 €

incl. 19% VAT.

Features:

EUROLITE LED SLS-6 TCL Spot

Flat spotlight with 6 x 8 W 3in1 LED with RGB color mixing

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 powerful LEDs 8 W high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 16°
- With mounting bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; small rental
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

ROADINGER Universal Case Pick TDV-1

Universal case with flexible foam dividers

- With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case

Technical specifications:

Weight: 8,09 kg

EUROLITE LED SLS-6 TCL Spot

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 15 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 6 x 8 W high-power 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0,5 - 23 Hz |
| DMX channels: | 2; 3; 4; 5; 7 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | 1 x cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function |
| Preprogrammed in: | EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 16° |
| Beam angle (1/2 peak): | 16° |
| Beam angle (1/10 peak): | 30° |
| Housing color: | Black matte |

| | |
|-------------------------|---|
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |
| Material: | Plastic; ABS Acrylonitrile butadiene styrene |
| Dimensions: | Width: 22 cm Depth: 11 cm Height: 21 cm |
| Weight: | 1,16 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Universal Case Pick TDV-1

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 12 mm |
| Carrying handle: | 1 pc/pcs |
| Stop hinge: | 3 pc/pcs |
| Lock: | Spring lock: 2 pc/pcs with shut-off function |
| Material: | Plastic, 3 mm |
| Color: | Black, imprinted |
| Inside dimensions: | 52 cm x 28,5 cm x 20 cm |
| Dimensions: | Width: 54 cm Depth: 31 cm Height: 26 cm |
| Weight: | 3,45 kg |