

EUROLITE Set 4x LED TL-4 Trusslight + Soft Bag

4x variable truss light and uplight with bright 4 x 8 W RGB+UV LED incl. soft bag

Art. No.: 2000636

GTIN:



List price: 565.25 €

incl. 19% VAT.

Features:

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUS 4-POINT SYSTEM QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 powerful LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; Sound to light via Microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Silent operation
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With Dividers
- With 2 Outside pockets
- With 4 Device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight: 6,76 kg

EUROLITE LED TL-4 QCL RGB+UV Trusslight

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 15 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| LED: | 4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4; 8 |
| DMX input: | 1 x USB, type A 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; Sound to light via Microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone |
| Preprogrammed in: | LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Beam angle: | 13° |
| Beam angle (1/2 peak): | 13° |
| Beam angle (1/10 peak): | 30° |
| Housing color: | Black |
| Attachment system: | M10 thread |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |

| | |
|-------------------------|--|
| Dimensions: | Length: 15,5 cm Width: 14,5 cm Height: 13,0 cm |
| Weight: | 1,56 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Power cord | |
| Cable construction: | 3 x 0,75 mm ² H05VV-F |
| Cable length: | Approx. 1,1 m |
| Color: | Black |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE SB-4 Soft Bag L

| | |
|-------------------------|---|
| Maximum load: | 25 kg |
| Carrying strap: | 2 pc/pcs |
| Material: | Nylon |
| Color: | Black, water repellent |
| Compartment dimensions: | 15 cm x 15 cm x 20 cm |
| Inside dimensions: | 31 cm x 34 cm x 20 cm |
| Dimensions: | Width: 32 cm Depth: 41 cm Height: 20 cm |
| Weight: | 520 g |