

## **EUROLITE Set 4x LED TL-4 Trusslight + Case**

4x variable truss light and uplight with bright 4 x 8 W RGB+UV LED incl. case

Art. No.: 20000638

GTIN:







List price: 593.81 €

incl. 19% VAT.

# Features: Logistic

#### **EUROLITE LED TL-4 QCL RGB+UV Trusslight**

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 powerful LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain;
   EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

#### **ROADINGER Universal Case Pick TDV-1**

Universal case with flexible foam dividers

- With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

  Package contents
- 1 x case

## **Technical specifications:**

Weight: 9,69 kg

#### **EUROLITE LED TL-4 QCL RGB+UV Trusslight**

Power consumption:  IP classification:  IP classification:  Protection class:  Protection class I  Power connection:  Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  LED type:  4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)  Flash rate:  0 - 20 Hz  DMX channels:  3; 4; 8  DMX input:  1 x USB, type A 1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (M) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickpMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/10 peak):  13°  Beam angle (1/10 peak):  4 x 8 W high-power 4 digit 7-segment LED display  Transport aid:  Rubber feet	Power supply:	100-240 V AC, 50/60 Hz
Protection class I  Power connection:  Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  LED type:  4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)  Flash rate:  0 - 20 Hz  DMX channels:  3; 4; 8  DMX input:  1 x USB, type A  1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/12 peak):  13°  Beam angle (1/10 peak):  4tachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Power consumption:	15 W
Power connection:  Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  LED type:  4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)  Flash rate:  0 - 20 Hz  DMX channels:  3; 4; 8  DMX input:  1 x USB, type A 1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); Stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/12 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	IP classification:	IP20
version power supply cord with safety plug (provided)  LED type:  4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)  Flash rate:  0 - 20 Hz  DMX channels:  3; 4; 8  DMX input:  1 x USB, type A  1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Protection class:	Protection class I
(homogenous color mix)  Flash rate: 0 - 20 Hz  DMX channels: 3; 4; 8  DMX input: 1 x USB, type A 1 x 3-pin XLR (M) mounting version  DMX output: 1 x 3-pin XLR (F) mounting version  Cooling: Passive convection cooling  Control: DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle: 13°  Beam angle (1/2 peak): 13°  Beam angle (1/10 peak): 30°  Housing color: Black  Attachment system: M10 thread  Display type: Monochrome 4 digit 7-segment LED display	Power connection:	version power supply cord with safety plug
DMX channels:  3; 4; 8  DMX input:  1 x USB, type A  1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/12 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	LED type:	
DMX input:  1 x USB, type A 1 x 3-pin XLR (M) mounting version  DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Flash rate:	0 - 20 Hz
1 x 3-pin XLR (M) mounting version  DMX output: 1 x 3-pin XLR (F) mounting version  Cooling: Passive convection cooling  Control: DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle: 13°  Beam angle (1/2 peak): 13°  Beam angle (1/10 peak): 30°  Housing color: Black  Attachment system: M10 thread  Display type: Monochrome 4 digit 7-segment LED display	DMX channels:	3; 4; 8
DMX output:  1 x 3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	DMX input:	1 x USB, type A
Cooling:  Passive convection cooling  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display		1 x 3-pin XLR (M) mounting version
Control:  DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	DMX output:	1 x 3-pin XLR (F) mounting version
control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone  Preprogrammed in:  LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle:  13°  Beam angle (1/2 peak):  13°  Beam angle (1/10 peak):  30°  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Cooling:	Passive convection cooling
DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief  Beam angle: 13°  Beam angle (1/2 peak): 13°  Beam angle (1/10 peak): 30°  Housing color: Black  Attachment system: M10 thread  Display type: Monochrome 4 digit 7-segment LED display	Control:	control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by
Beam angle (1/2 peak):  Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Preprogrammed in:	DELUXE; Light Captain; EASY SHOW 2; EASY
Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Beam angle:	13°
Housing color:  Attachment system:  M10 thread  Display type:  Monochrome 4 digit 7-segment LED display	Beam angle (1/2 peak):	13°
Attachment system: M10 thread  Display type: Monochrome 4 digit 7-segment LED display	Beam angle (1/10 peak):	30°
Display type: Monochrome 4 digit 7-segment LED display	Housing color:	Black
	Attachment system:	M10 thread
Transport aid: Rubber feet	Display type:	Monochrome 4 digit 7-segment LED display
	Transport aid:	Rubber feet

Dimensions:	Length: 15,5 cm
	Width: 14,5 cm
	Height: 13,0 cm
Weight:	1,56 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## **ROADINGER Universal Case Pick TDV-1**

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28,5 cm x 20 cm
Dimensions:	Width: 54 cm
	Depth: 31 cm
	Height: 26 cm
Weight:	3,45 kg