

OMNITRONIC PA Set AZX active M/L

2x active 18" PA bassreflex subwoofer with 2x active speaker with 12" woofer incl. distance tube

Art. No.: 20000644

GTIN:



List price: 2021.81 €

incl. 19% VAT.

Features:

OMNITRONIC AZX-118A PA Subwoofer active 400W

Active 18" PA bassreflex subwoofer, 400 W RMS

- 46 cm (18") bass speaker with 76 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Package contents

- 1 x bass, 1 x user manual, 1 x power cord

Logistic

OMNITRONIC AZX-212A 2-way Top active 250W

Active speaker with 12" woofer, 1,35" driver, 200 W RMS LF, 50 W RMS HF

- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- Balanced signal input XLR/6.3 mm jack, switchable mic/line
- HF adjustment -4 dB, -2 dB, 0 dB
- Dual flange
- With rigging points
- Black metal grille with acoustic foam
- Rugged carrying handle
- Application possibility: Standing; suspended; monitoring; on stand

- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Package contents

- 1 x user manual, 1 x power cord, 1 x compact cabinet speaker

OMNITRONIC Distance Tube Subwoofer/Satellite M20

Variable distance tube, M20 thread, height adjustable 75-130 cm, max. load 30 kg

- Connecting tube for satellite systems
- Locking screw and bolt
- Powder-coated steel version
- Adjustable height
- M20 thread

Package contents

- 1 x distance tube, 1 x user manual

Technical specifications:

Weight:	105,50 kg
---------	-----------

OMNITRONIC AZX-118A PA Subwoofer active 400W

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Power:	Rated: 400W RMS
Frequency range:	40 - 250 Hz
Sensitivity:	95 dB (1W/1m)
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 18" Basket material: steel Voice coil lows 2,5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted

Dimensions:	Width: 61,3 cm
	Depth: 61,3 cm
	Height: 54 cm
Weight:	32,70 kg

OMNITRONIC AZX-212A 2-way Top active 250W

Power supply:	230 V AC, 50 Hz
Power consumption:	650 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 200W RMS LF Rated: 50W RMS HF
Frequency range:	55 - 20000 Hz
Sensitivity:	95 dB (1W/1m)
Attachment system:	Dual flange: Ø 35mm (0°/5°)
Flying points:	7 x M10 thread
Circuitry:	Class D Biamp
Control elements:	Power switch, Input sensitivity switch, tone control, level control
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 1 x 3-pin XLR
Input channels:	1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Speaker:	Woofer 12" with ferrit magnet Basket material: steel Conematerial: cardboard/paper Voice coil lows 2" Voice coil compression tweeter highs 1,35"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 37 cm Depth: 35,2 cm Height: 62,2 cm
Weight:	19,15 kg

OMNITRONIC Distance Tube Subwoofer/Satellite M20

Maximum carrying capacity:	30 kg
Tube diameter sector:	41 - 35 mm

Height:	Maximum: 130 cm Minimum: 75 cm
Attachment system:	Ø 35mm
Type (general stands):	Distance tube
Color:	Black
Thread:	M20 thread
Weight:	0,90 kg