

EUROLITE Set 4x AKKU TL-3 TCL white + SB-4 Soft Bag

4x white spot for lighting within trussing, 3 x 3 W 3in1 LED including soft bag

Art. No.: 2000649

GTIN: 4026397670868



List price: 891.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via IR remote control; DMX; QuickDMX; Sound to light via Microphone; stand-alone
- Flicker-free
- With a beam angle of 11°
- For application areas such as: Small rental; Wedding/gala/events; mobile djs / entertainer; Stage
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397670868

Weight: 6,50 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With Dividers
- With 2 Outside pockets
- With 4 Device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight: 5,72 kg

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IEC connector (F) mounting version
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; DMX; QuickDMX; Sound to light via Microphone; stand-alone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°

Beam angle (1/10 peak):	24°
Housing color:	White
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 14,5 cm
Weight:	1,30 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	520 g