

EUROLITE Set 2x LED TMH-75 COB white + Case

2x bright spotlight and full-fledged washlight in white incl. PRO flightcase

Art. No.: 2000654

GTIN: 4026397670912



Features:

- Equipped with a white 75 W COB LED and nine 8 W 6in1LEDs in the colors red, green, blue, amber, white and UV
- Compact lightweight
- 7 brilliant, dichroic colors plus white
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 6 rotating gobos plus open
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer (0-100%)
- Motorized focus
- Programmable color-change speed and strobe effect
- Stepless color blend
- Color macros can be called up via DMX controller
- Exact positioning via 16-bit PAN/TILT movement resolution
- PAN angle switchable between 540°, 360° and 180°
- TILT angle switchable between 270°, 180° and 90°
- Stand-alone, master/slave and DMX mode
- Control panel with LC display for easy configuration
- 9 LEDs 8 W 6in1 RGBWA/UV (homogenous color mix)
- 1 LED 75 W COB (chip-on-board) color wheel (homogenous color mix)
- TILT angle switchable between 270° and 180°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Color wheel with 7 dichroic filters plus open

Logistic

EAN / GTIN: 4026397670912

Weight: 25,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Gobo wheel with rotating gobos, 6 gobos and open
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; DMX
- With a beam angle of 12°
- LCD display
- <p>ROADINGER Flightcase 2x LED TMH-75
- <h2 class="featureSatz">Trunk case with castors, HIGHLINE version</h2>With 1 Inlet tray for labeling panel
- High-quality workmanship with birch multiplex 9 mm,
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 41.50 kg

EUROLITE LED TMH-75 Hybrid Moving-Head Spot/Wash COB wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 8 W 6in1 RGBWA/UV (homogenous color mix) 1 x 75 W COB (chip-on-board) color wheel (homogenous color mix)
Max. TILT movement:	270°, 180° exact positioning (16 bit resolution) auto position correction (feedback); 90° positioning
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 6 gobos and open
DMX channels:	21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; DMX
Fixtures available for:	EASY SHOW 1; Light Captain; Light´J

Beam angle (1/2 peak):	Spot 12° Wash effect 28°
Illuminance in Lux (lx):	Wash effect red (R) 3m: 24 lx, 6m: 7 lx Wash effect green (G) 3m: 133 lx, 6m: 36 lx Wash effect blue (B) 3m: 20 lx, 6m: 6 lx Wash effect cold white (CW) 3m: 92 lx, 6m: 26 lx Wash effect amber (A) 3m: 31 lx, 6m: 9 lx Wash effect ultra violet (UV) 3m: 1 lx, 6m: 1 lx Wash effect all 3m: 288 lx, 6m: 78 lx Spot cold white (CW) 3m: 3942 lx, 6m: 1008 lx
Housing color:	White
Display type:	LCD display
Dimensions:	Width: 25.5 cm Depth: 25 cm Height: 31 cm
Weight:	8.20 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED TMH-75

Maximum load:	50 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 9 mm
Accessory compartment:	60.5 cm x 10.5 cm x 39 cm
Device compartment:	29 cm x 25 cm x 37 cm
Inside dimensions:	60.5 cm x 39.5 cm x 39 cm
Dimensions:	Length: 65 cm Depth: 44 cm Height: 73.5 cm
Weight:	25.10 kg

Scope of delivery:

- 1 x moving light
- 2 x omega bracket
- 4 x screw
- 1 x user manual
- 1 x power cord
- 1 x XLR cable