

EUROLITE Set 2x LED IP PAR 14x10W HCL + Case

2x weather-proof spotlight with RGBAW+UV color mixing and diffuser discs incl. PRO flightcase

Art. No.: 2000655

GTIN: 4026397670929



The article is no longer in our assortment.

Features:

EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 HCL RGBWA/UV color mixing and diffuser discs

- 14 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 3 x diffuser cover, 1 x xLR cable, 2 x knurled screw

Logistic

EAN / GTIN: 4026397670929

Weight: 25,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.75 m

Bulky product

ROADINGER Flightcase 2x TMH-30/40/60

PRO flightcase for 2 x EUROLITE LED TMH-30/TMH-40/TMH-60 moving-head

- For optimal security
- With 2 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 23,30 kg

EUROLITE LED IP PAR 14x10W HCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	14 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	3; 5; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°

Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Dimensions:	Width: 31 cm Depth: 22,5 cm Height: 36,5 cm
Weight:	7,05 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x TMH-30/40/60

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	26,5 cm x 31 cm x 30,5 cm
Middle compartment:	10,5 cm x 31 cm x 30,5 cm
Inside dimensions:	63,5 cm x 31 cm x 30,5 cm
Dimensions:	Width: 71 cm Depth: 35 cm Height: 40,5 cm
Weight:	9,20 kg